PermaPaper®

TECHNICAL DATA SHEET

ALL PRESSES · WATERPROOF PE · BS5609 ADHESIVE

DigiPlus Adhere

The most versatile label in the range. One stock for HP Indigo, inkjet, laser and dry toner.

DESCRIPTION

A polyolefin-based (PE) synthetic matt white film on an acrylic extra-permanent adhesive, with good performance in cold, moist conditions and strong adhesion to plastic and cardboard.

One-side coated kraft release liner with excellent stability on sheet-to-sheet digital printers. High thickness and dimensional stability support large-format labels.

APPLICATIONS

Drum and chemical labels · oil and chemicals · asset labels · warehouse and logistics · product ID · outdoor equipment · barcodes · durable shipping labels.

FEATURES

- Prints on HP Indigo, high-speed inkjet, laser and dry toner
- Waterproof, and resistant to tearing, chemicals and wear
- Permanent marine-grade adhesive, BS5609 compliant
- Suitable for indoor and outdoor use

PRODUCT INFORMATION

Product code	PPDPAS3XPSO
Size	SRA3, solid back
Pack	100 sheets
Printers	HP Indigo, inkjet, laser, dry toner

TYPICAL VALUES

Property	Unit	Method	Value
FACE MATERIAL PE DIGITAL MATT WHITE PE178			
Grammage	g/m²	ISO 536	115
Thickness	µm	ISO 534-80	178
Finish			Matt white
ADHESIVE EXTRA-PERMANENT XP33 · ACRYLIC			
Tack, glass	N	FTM 9	14
Peel value, glass · 24 hours	N/25mm	FTM 2	10
Minimum labelling temperature	°C		–5
Usage temperature	°C		–25 to +120
LINER 120G WHITE KRAFT			
Grammage	g/m²	ISO 536	120
Thickness	µm	ISO 534-80	113

CERTIFICATIONS

Complies with BS 5609, Section 2, Part 4.1 (marine performance type test).

Marine exposure.

PRINTING & CONVERTING

Follow the grain direction and use manual feed when laser printing to minimise curl. Test media, printer and inks before production.

Shelf life. 1 year in original closed packaging, stored per FINAT section 2.5 (20–25 °C, 40–50% RH).

Disclaimer. The information provided above is based on conclusive tests, which are indicative only and provided as guidelines. They do not constitute a guarantee of any specific product attributes or the suitability of products for specific applications.

sales@permapaper.co.uk 0203 337 2525 permapaper.co.uk

PermaPaper® is a registered trade mark.