

# ➔ GUILLOTINE IDEAL 4350

## CONVENIENT ELECTRIC GUILLOTINE WITH AUTOMATIC CLAMP AND 430 MM CUTTING LENGTH AND 435 MM TABLE DEPTH

**I** SCS - the Safety Cutting System made by IDEAL provides numerous safety features: hinged, electronically controlled safety guard on the front table; transparent safety cover on the rear table; main switch and safety lock with key; electronically controlled true two-hand operation; 24 volt control (low voltage); patented IDEAL safety drive; automatic blade and clamp return from every position; disc brake for instant blade stop; blade changing device with covered cutting edge; blade depth adjustment from the outside of the machine; easy blade change from the front of the machine without removing covers; cutting stick can be turned or replaced easily from the outside of the machine **I** 430 mm cutting length **I** cuts up to 500 sheets of paper (70 g/m<sup>2</sup>) or bound brochures up to 40 mm **I** electro-mechanical blade and clamp drive **I** blade made of german high quality steel **I** solid steel blade carrier **I** adjustable blade guides made of hardened steel **I** automatic clamp **I** precision side lay **I** spindle guided backgauge with hand crank **I** digital measurement readout for backgauge positioning (cm or inches) **I** optical cutting line with bright and durable LEDs **I** solid all-metal construction **I** designed as table top machine, a stand or a cabinet are available as option

Power supply: 230 V / 50 Hz / 1~<sup>1</sup>, Motor performance (input capacity): 0.45 kW

Dimensions (H x W x D): 360/1055<sup>1</sup>/1080<sup>2</sup> x 640 x 880 mm,

Weight: 86/96<sup>1</sup>/118<sup>2</sup> kg, Colour: pearl grey

<sup>1</sup> other voltages available

<sup>2</sup> with stand

<sup>3</sup> with cabinet



IDEAL 4350  
with cabinet as option



I.T.E. Listed 802 D

### SAFETY GUARDS



Transparent safety guards made from unbreakable plastic on front and rear table: The hinged front safety guard locks in the lower position while cutting.

### DIGITAL DISPLAY



Precise backgauge positioning with the hand crank is very easy due to the digital measurement readout, which can be switched over from cm to inch.

### SAFETY FIRST



The numerous features of SCS (Safety Cutting System) include a main switch, a true two-hand operation as well as an electric lock with key.

### ➔ IDEAL 4350

Cutting length	430 mm
Cutting height	40 mm
Narrow cut	35 mm
Table depth	435 mm
Digital display	cm/inches

# → GUILLOTINE IDEAL 4350 + ACCESSORIES

DESCRIPTION	ARTICLE NO.	EAN CODE
IDEAL 4350   230 V, 50 Hz*	43505011	4019364305511
Stand for IDEAL 4350	42051100	4019364201202
Cabinet for IDEAL 4350	42151100	4019364302206
Spare blade for IDEAL 4350	9000121	4019364920196
Cutting sticks for IDEAL 4350 (6 pieces per packing unit)	9000221	4019364925191

\* other voltages available

OPTIONAL STAND



BLADE CHANGING DEVICE



EASY CUTTING STICK CHANGE

