



Product Model

Gripple Loop End Fixing

End fixing that is ideal for looping around purlins, beams, roof trusses and other accessible building features.

Important Information

1. Construction materials and conditions vary on different sites. If it is suspected that the base material has insufficient strength to achieve a suitable fixing, contact Gripple Ltd. The responsibility for judgement of base material strength lies with the installer, and not with Gripple Ltd.
2. The information and recommendations given herein are believed to be correct at time of writing. The data has been obtained from tests done under laboratory, or other controlled conditions and it is the user's responsibility to use the data given in light of conditions on site, taking account of the intended use of the products concerned.
3. Whilst Gripple Ltd can give general guidance and advice, the nature of Gripple products means that the ultimate responsibility for selecting the correct product for a particular application must lie with the customer.
4. All products must be used, handled and applied in accordance with current product instructions and manufacturers' recommendations for use, published by Gripple Ltd.
5. Gripple's policy is one of continuous development and innovation. We, therefore reserve the right to alter specifications, etc. without notice.

Remark: This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way.

Technical data
supplied by the
manufacturer



Installation

- Pass the loop end over the building feature
- Thread the tail wire through the loop to create a choke knot
- Use Gripple to attach the service to the loop and adjust the height to complete the installation

Advantages

- Quick, simple choke-knot installation
- No need for nuts, bolts, clamps or other accessories
- Up to 6 times faster installation compared with threaded rod or chain
- Available in No.1 - No.5
- Supplied in a ready-to-use kit with a length of wire and a Gripple
- Also available in a Stainless Steel version

Loop Specification

	Loop Diam (mm)	Loop Length (mm)	Gripple Length (mm)	Gripple Width (mm)
No.1	30	60	60	60
No.2	30	60	60	60
No.3	26	60	60	60
No.4	46	85	85	85
No.5	46	90	90	90

Solutions, Service and Supplies to the Trade

Springhead Enterprise Park, Springhead Road, Northfleet, Kent DA11 8HJ

T 01322 274226 F 01322 278178 E sales@fixmart.co.uk www.fixmart.co.uk

