



Product Model

ODE Starflex Duct Blanket VKM AFH D-24

Thermal insulation products for building equipment and industrial installations - Factory made mineral wool. Glasswool - bonded with a thermosetting resin, flexible, for thermal and sound insulation. Aluminium Foil Faced.

Packing

- 1 Blanket in package
- 21,60 (m² /package)
- Up to 4 hours fire resistance
- LDPE package

Technical Data

			Test Method
Thickness (mm)	25		EN 823
Length (mm)	18000		EN 822
Width (mm)	1200		EN 822
Density (kg/m ³)	24		EN 1602

Technical data supplied by the manufacturer



Storage

- Store in dry and well ventilated area prior to installation
- Protect from water, physical damage and direct flame sources

Tolerances

			10 °C	50 °C	100 °C	150 °C	200 °C
Thermal Conductivity	EN 12939	W/(m.K)	0,035	0,040	0,050	0,060	0,075
Thermal Resistance	EN 12939	(m ² .K)/W	0,700	0,600	0,500	0,400	0,300
Fire Resistance Class	EN 13501-1	Euroclass	A1	A1	A1	A1	A1
Maximum Service Temperature	-	°C	250	250	250	250	250
Short Term Water Absorption	EN 1609	kg/m ²	1 >	1 >	1 >	1 >	1 >

Remark: This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way.

Solutions, Service and Supplies to the Trade

Springhead Enterprise Park, Springhead Road, Northfleet, Kent DA11 8HJ

T 01322 274226 F 01322 278178 E sales@fixmart.co.uk www.fixmart.co.uk