

Product Model
Gasket Tape: Butyl

Butyl Gasket tape is a pre-formed strip of 100% polymeric, butyl rubber compound which assures virtually airtight joints. It bonds immediately to the mating flanges without slippage or movement.



Technical data supplied by the manufacturer



Uses

Typical applications include sealing of duct flanges and laps in ductwork, especially on ductwork subject to pressure testing carried out at 1000Pa or over. Self adhesive sealant may be considered as a void filling adhesive. It was developed to provide a tough, durable metal lap joint seal against the ingress of water, dirt and the like.

| Widths | Standard length | Service temperature | Flexibility | Stability | Aging |
|-----------------------|----------------------------|---------------------|---|---|--|
| 9mm wide x 4mm thick | 10m (9 & 15) 8m (19 & 2.5) | -50°C to + 105°C | Infinite at room temperature, excellent at low temp | Will not flow, slump or drip even at +105 | Retains excellent flexibility with no apparent loss of adhesion to galvanised steel, aluminium or painted substrates |
| 15mm wide x 4mm thick | | | | | |
| 19mm wide x 3mm thick | | | | | |
| 25mm wide x 5mm thick | | | | | |
| 25mm wide x 5mm thick | | | | | |

Remark: This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way.