



Product Model

Arboseal Intumescent Tape

Arboseal Intumescent Tape is a flat section, preformed Intumescent strip based upon synthetic rubbers and carefully chosen fire resistant materials. It deforms under moderate pressure and has appreciable surface tack and recovery. When subject to flame, Arboseal Intumescent Tape will intumesce (expand and char) blocking the passage of fire and smoke.

Technical data supplied by the manufacturer



Main Applications

Recommended for use in glazing internal and external FD30 timber fire doors and screens.

NB: Not recommended for external use without a sealant capping (please contact Adshead Ratcliffe Technical Service Department for further information.) Not recommended for use in expansion joints.

Specification Compliance

BS476 Part 22:1987;

Warrington Report Number: C118002

TRADA Report Number: IT349

Health and Safety

No known health hazards associated with this product. Please consult Material Safety Data Sheet for full information.

Packaging

Size: 15mm x 3 mm x 12 metres per reel.

Storage Life

12 months in original unopened packaging stored in a cool, dry place out of direct sunlight

Accessories

Cleaners: Arbo Cleaner No.17- 1 Litre Tin (Xylene based – not suitable for use with plastics or delicate finishes)

Cleaners: Arbo Cleaner No. 16 - 1 Litre Tin (Alcohol Based)

Important

The information in this leaflet is given in good faith and based on results gained from experience and tests.

However, all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Goods are supplied subject to the Company's terms and conditions of sales, a copy of which is available on request.

Arbo sealants are manufactured in the U.K. by Adshead Ratcliffe

Technical Data

Application Temperature	+ 5°C to + 50°C
Service Temperature	- 25°C to + 50°C
Chemical Resistance	Fair resistance to most dilute acids and alkalis, vegetable oils and alcohol. Poor resistance to hydrocarbon solvents.
UV Resistance	Good
Service Life	20 years+
Colours	Teak, White

Remark: This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way.

Solutions, Service and Supplies to the Trade

Springhead Enterprise Park, Springhead Road, Northfleet, Kent DA11 8HJ

T 01322 274226 F 01322 278178 E sales@fixmart.co.uk www.fixmart.co.uk