



## Product Model Fixed Height Frames (335mm high)

Non adjustable frames offer a simple solution for mounting plant on flat roofs. The frames are made from 40mm x 40mm galvanised box section giving you a very durable system. The frames come in a full range of widths from 600mm to 2 metres utilising a common 1.2metres long sliding mounting. The common rails are locked into position using 2 x M8 Nuts & Bolts, which creates a simple clamping action. With our twin claw foot it is easy to join 2 frames together if a larger system is required onsite.

Technical data supplied by the manufacturer



Frames are manufactured from 40mm x 40mm x 2.5mm wall thickness -Galvanised SHS – BS EN ISO 1461

Stock Code	Description	Length (mm)	Height inc. Foot (mm)
331102558	600 Rigid Frame	680	335
331102559	800 Rigid Frame	880	335
331102560	1000 Rigid Frame	1080	335
331102561	1500 Rigid Frame	1580	335
331102562	2000 Rigid Frame	2080	335

### Optional Extra's for Adapting Frames

Stock Code	Description
331202567	Single Core Foot (Pair)
331202566	Double Core Foot (Pair)
331102563	Twin Claw Foot (Pair)
331102552	1.2m Common Rail

**Remark:** This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way.



### Solutions, Service and Supplies to the Trade

Springhead Enterprise Park, Springhead Road, Northfleet, Kent DA11 8HJ

T 01322 274226 F 01322 278178 E sales@fixmart.co.uk www.fixmart.co.uk

