Fixmart Data Sheet V01



Product Model

Stud screw STST with torx

Machine thread at one end, coach screw thread at the other end with spanner flats between.

Properties

- Material: steel 4.6 acc. to DIN EN ISO 898-1
- Zinc plating: electro zinc-plated, min. 3 μm

Technical data supplied by the manufacturer



Advantages / Benefits

Fixing with a Nylon plug to brick or direct into timber construction is simple with the torx drive or the integrated hexagon.

Applications

- Threaded connectors stud screw STST
- Wood and metric screw combination for direct installation of clamps onto a wall

Article name	Art. No.	Length (mm)	Thread	Drive
STST 6 x 60	504400	60	M6	T15
STST 6 x 60	077714	80	M6	T15
STST 8 x 50	079780	50	M8	T25
STST 8 x 60	079781	60	M8	T25
STST 8 x 80	079782	80	M8	T25
STST 8 x 100	079783	100	M8	T25
STST 8 x 120	079784	120	M8	T25
STST 8 x 140	079785	140	M8	T25
STST 8 x 180	079786	180	M8	T25
STST 10 x 60	077689	60	M10	T25
STST 10 x 80	077707	80	M10	T25
STST 10 x 100	077708	100	M10	T25
STST 10 x 120	077709	120	M10	T25
STST 10 x 140	077711	140	M10	T25
STST 10 x 180	077712	180	M10	T25

Remark: This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way.

