



**Product Model**  
**Protective Sleeve tubing**

Technical data  
 supplied by the  
 manufacturer



**Recommended Applications**

- Oval Duct
- Piping
- Rectangular Duct
- Spiral Duct

**Features / Benefits**

- Creates a barrier against adverse reactions between dissimilar metals
- Ideal for use with Gripple hanger kits on spiral or oval ducting
- Available in black, white or clear as standard
- Available in two sizes, 2mm and 3mm in lengths of 25m

**Submittal Information**

<b>Material</b>	Clear flexible PVC compound
<b>Colour</b>	Clear and tints
<b>Application</b>	Low toxicity, food contact and general purpose extrusions
<b>Specification</b>	Free from Substances of Very High Concern as described under REACH regulation. Material complies with the migration requirements of 002/72/EC and its amendments.
<b>Form</b>	Granules
<b>Density</b>	(varies with colour) kg/m <sup>3</sup> 1218 (Clear 181) Shore "A" Hardness (15 secs @ 23o C) Shore "A" 74 Tensile Strength @ 500 mm/min MPa 15.3 Elongation at Break @ 500 mm/min % 315
<b>Cold Flex Temperature</b>	o C -39
<b>BS Softness</b>	BSSo 45
<b>Properties Units          Typical Test Results</b>	(These values do not form part of a specification) (Based on B.S. 2782 methods)
<b>Overall Specific Migration</b>	Material tested to current EC regulations (directive 2002/72/EC and its amendments) using a total immersion method (EN1186, part 3) in 50% ethanol at 40°C for time periods of 10 mins and 1 hour. 50% Ethanol, 10 mins @ 40°C mg/dm <sup>2</sup> 1.1 50% Ethanol, 1 hour @ 40°C mg/dm <sup>2</sup> 2.1

**Solutions, Service and Supplies to the Trade**

Springhead Enterprise Park, Springhead Road, Northfleet, Kent DA11 8HJ  
 T 01322 274226 F 01322 278178 E sales@fixmart.co.uk [www.fixmart.co.uk](http://www.fixmart.co.uk)

