



Product Model Partex Masonry Mounts

Our high quality masonry mounts are made from black Nylon 6.6 and are designed to secure cable ties directly to holes drilled in solid surfaces. Supplied in bags of 100.

Available in two sizes

MM6	to suit a 6.0mm pre-drilled hole.
MM7	to suit a 7.0mm pre-drilled hole.

Material	Black Nylon 6.6*
Temperature range	-40°C to +85°C
Maximum cable tie width	9.0mm
Fixing hole depth	38.0mm

Technical data
supplied by the
manufacturer



*Nylon 6.6 is a tough, relatively strong material, which possesses good fatigue resistance, low coefficient of friction, good thermal stability and low flammability. It is noted for its resistance to chemicals, especially hydrocarbons and greases. Partex masonry mounts are manufactured from black material which is resistant to UV radiation, and are therefore suitable for exposure to sunlight and exterior weather conditions.

Remark: This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way.