## **Product Model**

# Scapa 3159 Waterproof Cloth Tape

Scapa 3159 is an economy grade, polyethylene laminated cloth tape, coated with a pressure sensitive adhesive.

Scapa 3159 is available in silver, black and white only.



Technical data supplied by the manufacturer



#### **Applications**

Designed as a general purpose cloth tape for a full range of industrial and construction applications:

- Sealing
- Bundling
- Short temrma sking
- Protection

## Product Benefits

- Good water resistance
- Good adhesion and strength
- Flexible and conformable
- Good low temperature performance
- Good all purpose product
- Service temperature -10 to +75°C

### **Technical Properties**

	Unit	Nominal Value	Test Method
Thickness mm		0.14	AFERA 5006*
Tensile Strength	N/cm	35	IEC 454-2
Adhesion to Steel	N/cm	4	IEC 454-2
Adhesion to backing	N/cm	2.5	IEC 454-2

<sup>\*</sup> Scapa Internal Test Method to measure thickness now replaced by the more rigorous AFERA method.

### **Standard Presentation**

Roll Length	50m	
Roll Width	48mm and 72mm only	
Core	Plain Cardboard	
Colours	Black, white and silver	
Packaging	Shrink – wrapped in packs of 4 with 6 packs to a carton (48mm) / Shrink – wrapped in packs of 4 with 4 packs to a carton (72mm)	

<sup>\*</sup> Scapa Internal Test Method to measure thickness now replaced by the more rigorous AFERA method.







# **Fixmart Data Sheet V01**

#### Recommendations

The rolls should be stored flat on their cut edges in the original packaging, until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Shelf life will vary with conditions of use and is affected by climate environment, but should not be less than two years from date of manufacture, if stored in a moderate climate and good conditions.

Remark: This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way.

