



## Benefits

- Enables friction to be reduced between most surfaces
- Eliminates noise and squeak
- Leaves a bright gloss finish to vinyl
- All-Purpose Silicone Spray meets BS6920 for use in contact with potable drinking water.

## Areas For Use

- Multitude of uses in the mould making and mould release industries
- Making easy the installation of EPDM gaskets to window and doorframes.
- Restoring the black gloss finish to car vinyl trim without the need for polishing
- As a general high quality spray lubricant.

## Application

Shake the can and spray as required directly onto surface(s) to be lubricated. When used as a mould release agent, spray liberally onto mould and allow to dry.

Coverage: 120-250g/m<sup>2</sup>

**Shelf Life:** 12 months.

**Remark:** This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way.

## Product Model

### All Purpose Silicone Spray

Everbuild All-Purpose Silicone Spray is a dry silicone lubricant and mould release agent for the easing of friction between two surfaces. All-Purpose Silicone Spray is ideal for use in mould making/release industries, to ease installation of rubber and EPDM gaskets to window and door frames and has 100's of uses around the home, garage, workshop and industry. All-Purpose Silicone Spray will also enhance the appearance of vinyl and hard surfaces such as car dashboards etc, where the dry-bright finish will eliminate the need to polish.

Product Code	Pack Size	Box Qty
SILSPRAY	400ml	12

Technical data supplied by the manufacturer



## Limitations

Do not ingest. Pressurized container – Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn even after use. Do not spray on a naked flame or incandescent material. Test small area of surface to be coated for compatibility before use. As the manufacturer cannot know all the uses its products may be put to, it is the users responsibility to determine suitability of use. If in doubt, contact Technical Services Department for advice

## Health & Safety

Extremely flammable

Keep out of reach of children

If swallowed, seek medical advice immediately and show this container/label. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Do not breathe vapour/spray.

Keep away from sources of ignition – no smoking.

## Storage

Store in original packaging away from direct sunlight and sources of ignition between 5 and 25°C.

## Solutions, Service and Supplies to the Trade

Springhead Enterprise Park, Springhead Road, Northfleet, Kent DA11 8HJ

T 01322 274226 F 01322 278178 E sales@fixmart.co.uk [www.fixmart.co.uk](http://www.fixmart.co.uk)

