



Product Model

GB500 - Gloss Black

MB500 - Matt Black

Product Type	Nitro Combi
Coverage	1.56 - 2.19m ² per 500ml
Drying times	
Dust Free	5 - 10minutes
Touch Dry	10 - 20 minutes
Overcoatable	after 2 hours

The drying time depends on temperature, humidity and the thickness of the applied coat.

Technical data
supplied by the
manufacturer

PRO-MATIC[®]

Products Characteristics

- Fast drying product with good spray characteristics
- Suitable for internal and external use
- Weather resistant, light proof and UV resistant
- Scratch and impact resistant
- Excellent surface hardness and good elasticity
- Can be mechanically polished

Surface Preparation

Prior to applying the topcoat, apply a suitable primer.

The surface must be free from all contamination including rust, grease and moisture. Before use, carefully read and note the warning text on the label.

Remark: This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way.

Solutions, Service and Supplies to the Trade

Springhead Enterprise Park, Springhead Road, Northfleet, Kent DA11 8HJ

T 01322 274226 F 01322 278178 E sales@fixmart.co.uk www.fixmart.co.uk