



Product Model GP500 – Grey Primer

Product Type	Nitro Combi
Coverage	1.56 - 2.19m ² per 500ml
Drying times	
Dust Free	5 - 10minutes
Touch Dry	10 - 20 minutes
Sandable	after 2 hours
Overcoatable	after 2 hours

The drying time depends on temperature, humidity and the thickness of the applied coat.

Technical data
supplied by the
manufacturer

PROnMATIC[®]

Products Characteristics

- Excellent corrosion prevention
- Optimizes the gloss finish of the topcoat
- Fast drying with good spraying properties and good coverage
- Excellent adhesion of subsequent topcoat
- Excellent filling properties and easy to sand
- Will adhere to wood, metal, aluminium and many other substrates.

Surface Preparation

- De-rust, abrade and clean surfaces prior to coating
- The surface must be free from all contamination including rust, grease and moisture.
- Before use, carefully read and note the warning text on the label

Remark: This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way.

Solutions, Service and Supplies to the Trade

Springhead Enterprise Park, Springhead Road, Northfleet, Kent DA11 8HJ

T 01322 274226 F 01322 278178 E sales@fixmart.co.uk www.fixmart.co.uk