



ECOPROTEC SATIN FINISH SURFACE WAX SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : ECO SATIN FINISH SURFACE WAX

Product code : ECO/10

1.2. Relevant identified uses of the substance or mixture and uses advised against

Protection for tiling

1.3. Details of the supplier of the safety data sheet

Marketing Company and Distributor

LTP

Tone Ind Estate, Milverton Road

Wellington. TA21 0AN

Tel: 01823 666213 info@ltp-online.co.uk www.ltp-online.co.uk

1.4. Emergency telephone number : + 44 (0) 1823 666213

Office hours only 8.30-5.30pm

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS07

Signal Word :

WARNING

Product identifiers :

EC 254-099-2 CARBONATE DE TETRAAMMINEZINC (2+)

613-326-00-9 2-METHYLISOTHIAZOL-3(2H)-ONE

EC 220-120-9 1,2-BENZISOTHIAZOL-3(2H)-ONE

EC 611-341-5 MIXTURE OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE [EC NO. 247-500-7] AND
2-METHYL-2HISOTHIAZOL-3-ONE [EC NO. 220-239-6] (3:1)

Hazard statements :

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements - General :

P102 Keep out of reach of children.

Precautionary statements - Prevention :

P262 Do not get in eyes.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response :

P302 + P352 IF ON SKIN: Wash with plenty of water and soap.

ECOPROTEC SATIN FINISH SURFACE WAX

| | |
|---------------------------------------|---|
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P333 + P313 | If skin irritation or rash occurs: Get medical advice/attention. |
| P337 + P313 | If eye irritation persists: Get medical advice/attention. |
| Precautionary statements - Disposal : | |
| P501 | Dispose of contents/container in conformity with national legislation in vigour. The empty packaging and unused contents are to be disposed of at a waste collection point. |

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

| Identification | (EC) 1272/2008 | Note | % |
|---|--|------|---------------------|
| INDEX: 34590948 CAS: 34590-94-8 EC: 252-104-2 REACH: 01-2119450011-60 DIPROPYLENE GLYCOL MONOMETHYLIQUE ETHER | | [1] | 2.5 \leq x % < 10 |
| INDEX: 2530838 CAS: 2530-83-8 EC: 219-784-2 REACH: 01-2119513212-58-0002 (3-(2,3-ÉPOXYPROPOXY)PROPYL)TRIMÉT HOXYSILANE | GHS05 Dgr Eye Dam. 1, H318 | | 0 \leq x % < 2.5 |
| INDEX: 38714_475 CAS: 38714-47-5 EC: 254-099-2 CARBONATE DE TETRAAMMINEZINC (2+) | GHS07, GHS09 Wng Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1 | | 0 \leq x % < 2.5 |
| INDEX: 613-326-00-9 CAS: 2682-20-4 EC: 220-239-6 2-METHYLISOTHIAZOL-3(2H)-ONE | GHS06, GHS05, GHS09 Dgr Acute Tox. 3, H301 Acute Tox. 3, H311 Skin Corr. 1B, H314 Skin Sens. 1A, H317 Eye Dam. 1, H318 Acute Tox. 2, H330 Aquatic Acute 1, H400 M Acute = 10 Aquatic Chronic 1, H410 M Chronic = 1 EUH:071 | | 0 \leq x % < 2.5 |
| INDEX: 613_088_006B CAS: 2634-33-5 EC: 220-120-9 1,2-BENZISOTHIAZOL-3(2H)-ONE | GHS06, GHS05, GHS09 Dgr Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Dam. 1, H318 Acute Tox. 2, H330 Aquatic Chronic 2, H411 Aquatic Acute 1, H400 M Acute = 1 | | 0 \leq x % < 2.5 |

ECOPROTEC SATIN FINISH SURFACE WAX

| | | | |
|---|---|--|----------------|
| INDEX: 613_167_00AB CAS: 55965-84-9 EC: 611-341-5 MIXTURE OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE [EC NO. 247-500-7] AND 2-METHYL-2HISOTHIAZOL-3-ONE [EC NO. 220-239-6] (3:1) | GHS06, GHS05, GHS09 Dgr Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1B, H314 Skin Sens. 1, H317 Acute Tox. 2, H330 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1 | | 0 <= x % < 2.5 |
|---|---|--|----------------|

(Full text of H-phrases: see section 16)

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Seek medical attention immediately, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)
- nitrogen oxide (NO)
- nitrogen dioxide (NO₂)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

ECOPROTEC SATIN FINISH SURFACE WAX

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Fire prevention :

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid skin and eye contact with this mixture.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union (2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

| CAS | VME-mg/m3 : | VME-ppm : | VLE-mg/m3 : | VLE-ppm : | Notes : |
|------------|-------------|-----------|-------------|-----------|---------|
| 34590-94-8 | 308 | 50 | - | - | Peau |

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

| CAS | TWA : | STEL : | Ceiling : | Definition : | Criteria : |
|------------|---------|---------|-----------|--------------|------------|
| 34590-94-8 | 100 ppm | 150 ppm | | Skin | |

- Germany - AGW (BAuA - TRGS 900, 08/08/2019) :

| CAS | VME : | VME : | Excess | Notes |
|------------|-------|---------------------------------|--------|-------|
| 34590-94-8 | | 50 ppm 310 mg/m ³ | | 1(I) |

- France (INRS - ED984 / 2019-1487) :

| CAS | VME-ppm : | VME-mg/m3 : | VLE-ppm : | VLE-mg/m3 : | Notes : | TMP No : |
|------------|-----------|-------------|-----------|-------------|---------|----------|
| 34590-94-8 | 50 | 308 | - | - | * | 84 |

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

| CAS | TWA : | STEL : | Ceiling : | Definition : | Criteria : |
|------------|---------------------------------|------------------------------|-----------|--------------|------------|
| 34590-94-8 | 50 ppm 308 mg/m ³ | - ppm - mg/m ³ | | Sk | |

ECOPROTEC SATIN FINISH SURFACE WAX

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

DIPROPYLENE GLYCOL MONOMETHYLIQUE ETHER (CAS: 34590-94-8)

Final use:

Exposure method:
Potential health effects:
DNEL :

Workers.

Dermal contact.
Long term systemic effects.
65 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
310 mg of substance/m³

Final use:

Exposure method:
Potential health effects:
DNEL :

Consumers.

Ingestion.
Long term systemic effects.
1.67 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Dermal contact.
Long term systemic effects.
15 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
37.2 mg of substance/m³

Predicted no effect concentration (PNEC):

DIPROPYLENE GLYCOL MONOMETHYLIQUE ETHER (CAS: 34590-94-8)

Environmental compartment:
PNEC :

Soil.
2.74 mg/kg

Environmental compartment:
PNEC :

Fresh water.
19 mg/l

Environmental compartment:
PNEC :

Sea water.
1.9 mg/l

Environmental compartment:
PNEC :

Intermittent waste water.
190 mg/l

Environmental compartment:
PNEC :

Fresh water sediment.
70.2 mg/kg

Environmental compartment:
PNEC :

Marine sediment.
7.02 mg/kg

Environmental compartment:
PNEC :

Waste water treatment plant.
4168 mg/l

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

ECOPROTEC SATIN FINISH SURFACE WAX

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVC (polyvinyl chloride)

- Butyl Rubber (Isobutylene-isoprene copolymer)

- PVA (Polyvinyl alcohol)

Recommended properties :

- Impervious gloves in accordance with standard EN ISO 374-2

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

| | |
|------------------|---------------|
| Physical state : | Fluid liquid. |
| Colour | Beige |
| Odours | Flowery |

Important health, safety and environmental information

| | |
|---|-----------------|
| pH : | 8.50 . |
| | Slightly basic. |
| Boiling point/boiling range : | Not relevant. |
| Flash point interval : | Not relevant. |
| Vapour pressure (50°C) : | Not relevant. |
| Density : | > 1 |
| Water solubility : | Dilutable. |
| Melting point/melting range : | Not relevant. |
| Self-ignition temperature : | Not relevant. |
| Decomposition point/decomposition range : | Not relevant. |

9.2. Other information

No data available.

ECOPROTEC SATIN FINISH SURFACE WAX

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid :

- frost

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)
- nitrogen oxide (NO)
- nitrogen dioxide (NO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

May cause an allergic reaction by skin contact.

2-butoxyethanol and its acetate are absorbed directly through the skin and have harmful effects on the blood.

11.1.1. Substances

Acute toxicity :

DIPROPYLENE GLYCOL MONOMETHYLIQUE ETHER (CAS: 34590-94-8)

Oral route : LD₅₀ > 2000 mg/kg

Dermal route : LD₅₀ > 2000 mg/kg

Inhalation route (Dusts/mist) : LC₅₀ > 20 mg/l

11.1.2. Mixture

No toxicological data available for the mixture.

Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 5989-27-5 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

SECTION 12 : ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

DIPROPYLENE GLYCOL MONOMETHYLIQUE ETHER (CAS: 34590-94-8)

Fish toxicity : LC₅₀ = 10000 mg/l
Species : Pimephales promelas
Duration of exposure : 96 h

Crustacean toxicity : EC₅₀ = 1919 mg/l
Duration of exposure : 48 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

ECOPROTEC SATIN FINISH SURFACE WAX

12.2. Persistence and degradability

12.2.1. Substances

DIPROPYLENE GLYCOL MONOMETHYLIQUE ETHER (CAS: 34590-94-8)
Chemical oxygen demand : DCO = 0.00202 g/g

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number

-

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

-

14.4. Packing group

-

14.5. Environmental hazards

-

14.6. Special precautions for user

-

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2018/1480 (ATP 13)

- Container information:

No data available.

- Particular provisions :

No data available.

ECOPROTEC SATIN FINISH SURFACE WAX

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

| | |
|--------|---|
| H301 | Toxic if swallowed. |
| H302 | Harmful if swallowed. |
| H310 | Fatal in contact with skin. |
| H311 | Toxic in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H330 | Fatal if inhaled. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |
| EUH071 | Corrosive to the respiratory tract. |

Abbreviations :

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.