



SAFETY DATA SHEET

Stone Oil

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name Stone Oil
Product No. WTCT001, WTCT005
Internal Id 0375

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Oil based polish sealer.
Uses Advised Against Any use other than those identified.

1.3. Details of the supplier of the safety data sheet

Supplier: LTP
Tone Industrial Estate
Milverton Road
Wellington
Somerset
TA21 0AN
Tel: 01823 666213
Fax: 01823 665685

1.4. Emergency telephone number

0870 190 6777

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards	Not classified.
Human health	EUH066; Asp. Tox. 1 - H304
Environment	Aquatic Chronic 2 - H411

Classification (1999/45/EEC)

Xn;R65. N;R51/53. R66.

Human Health

Prolonged or repeated contact with skin may cause redness, itching, irritation, eczema, skin cracking and oil acne. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Environment

The product contains a substance which is toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

Physical And Chemical Hazards

Rags, paper, sawdust or other combustible materials impregnated with this product may spontaneously ignite. After use any rags or cloths should ideally be burned. If this is not possible they should be washed in warm soapy water. Even after washing they should never be crumpled into a ball but spread out and disposed of.

2.2. Label elements

Contains: White Spirit : (naphtha (petroleum), hydrodesulphurised heavy (<0.1% benzene))
Label In Accordance With (EC) No. 1272/2008

Stone Oil



Signal Word	Danger	
Hazard Statements	H304	May be fatal if swallowed and enters airways.
	H411	Toxic to aquatic life with long lasting effects.
Precautionary Statements	P102+405	Store locked up. Keep out of reach of children.
	P273	Avoid release to the environment.
	P261e	Avoid breathing vapours.
	P301+P331+P315	If SWALLOWED: Do NOT induce vomiting. Get immediate medical advice/attention.
	P501A	Keep away from food, drink and animal feedingstuffs. Dispose of contents/container in accordance with local authority requirements.
Supplemental Label Information (EU)	EUH066	Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

White Spirit : (naphtha (petroleum), hydrodesulphurised heavy (<0.1% benzene))	30-60%
CAS-No.: 64742-82-1	EC No.: 265-185-4
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC) Xn;R65. N;R51/53. R10,R66.

The Full Text for all R-Phrases and Hazard Statements is Displayed in Section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Information

Remove affected person from source of exposure. Provide fresh air, first-aid, warmth and rest.

Do not give victim anything to drink if they are unconscious.

Inhalation.

Clean nose and mouth with water. If unconscious or breathing is irregular artificial respiration may be administered by suitably qualified first-aiders.

Get medical attention if symptoms persist.

Ingestion

If swallowed do NOT induce vomiting. Never give anything by mouth to an unconscious person. If patient vomits keep head low to prevent vomit entering lungs. If conscious give 1 - 2 glasses of water to drink.

Rinse mouth thoroughly and seek medical attention immediately. Keep patient at rest.

Skin Contact

Remove contaminated clothing and shoes. Wash skin thoroughly with soap and running water. Take especial care to clean folds, crevices, creases and groin.

Get medical attention if irritation persists or develops.

Launder clothing and clean shoes thoroughly before re-use.

Stone Oil

Eye Contact

Check for contact lenses which must be removed from the eyes before rinsing.
Promptly rinse eyes with plenty of clean water while lifting the eyelids.
Continue to rinse for at least 15 minutes. Continue until the eyes are free of all traces of contamination.
Get medical attention if any discomfort or irritation persists.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing Media

Use fire-extinguishing media appropriate for surrounding materials. Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

Rags, paper, sawdust or other combustible materials impregnated with this product may spontaneously ignite in contact with air or oxidising materials.

5.3. Advice for firefighters

Protective Measures In Fire

Wear self-contained breathing apparatus and full protective clothing. Keep all unnecessary people away.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing (see Section 8). Keep unnecessary people at a safe distance. In case of spills, beware of slippery floors and surfaces. Combustible materials impregnated with this product which are allowed to dry out may spontaneously ignite. Contaminated clothing should be kept moist and laundered before re-use.

6.2. Environmental precautions

Cover all drains and sewers. Avoid spreading spilt material.

6.3. Methods and material for containment and cleaning up

Ventilate well. Extinguish all ignition sources. Avoid sparks, flames, heat. No smoking. Keep flammable materials away from spillage. Clean-up personnel should use respirator and liquid contact protection.
Absorb in vermiculite, dry sand or earth and place into containers. Wash well after dealing with spillage. Inform authorities if large amounts are involved.
Rinse site with copious amounts of water, which should not be allowed into drains, sewers or water courses.

6.4. Reference to other sections

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Avoid prolonged or repeated contact, use suitable protective goggles, gloves and clothing. (see section 8).

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
White Spirit : (naphtha (petroleum), hydrodesulphurised heavy (<0.1% benzene))	WEL		1000 mg/m ³			

WEL = Workplace Exposure Limit.

Stone Oil

8.2. Exposure controls

Engineering Measures

Provide adequate general and local exhaust ventilation.

Respiratory Equipment

If ventilation is insufficient suitable respiratory protection must be provided.

Seek recommendations and advice from equipment manufacturer or supplier.

Hand Protection

Wear suitable protective gloves conforming to EN 374. Seek recommendations from manufacturer or supplier. After using gloves the hands should be washed and dried thoroughly and a suitable moisturiser applied. Suitable gloves may include - Nitrile. Viton rubber (fluor rubber).

Eye Protection

Use eye protection.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene Measures

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet.

Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Straw coloured liquid
Odour	Solvent.
Solubility	Immiscible with water
Relative Density	0.85 - 0.88
Flash Point (°C)	>61 CC (Closed cup).
Auto Ignition Temperature (°C)	>240
Flammability Limit - Lower(%)	0.8
Flammability Limit - Upper(%)	6

9.2. Other information

Volatile Organic Compound (VOC)	>30 % (EC/1999/13)
---------------------------------	--------------------

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

10.2. Chemical stability

Stable under normal conditions of storage and use. See section 7.

10.3. Possibility of hazardous reactions

Polymerisation Description

May polymerise at room temperature when in contact with air or other oxidisers, leading to evolution of heat and subsequent spontaneous ignition of combustible materials. (See section 2)

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials To Avoid

Strong oxidising agents, acids and bases. Flammable/combustible material.

10.6. Hazardous decomposition products

Decomposition can lead to the formation of toxic gases or fumes, including carbon monoxide (CO) and carbon dioxide (CO₂)

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Stone Oil

Toxicological Information

No data is available for this preparation, which is classified according to the calculation method of EC Directive 88/379/EEC.

Inhalation

Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion.

Harmful: may cause lung damage if swallowed. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

Skin Contact

Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

Eye Contact

May cause severe irritation to eyes.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

The product contains a substance which is toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

12.1. Toxicity

12.2. Persistence and degradability

Degradability:

The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative Potential:

The product contains potentially bioaccumulating substances.

12.4. Mobility in soil

Mobility:

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: DISPOSAL CONSIDERATIONS

General Information

Product is hazardous waste. Do not allow into drains, sewers or water courses.

Disposal must be by means of a licensed waste contractor.

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

UN No. (ADR/RID/ADN)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263

14.2 UN Proper shipping name

Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (White Spirit : (naphtha (petroleum), hydrodesulphurised heavy (<0.1% benzene)))

14.3 Transport hazard class(es)

ADR/RID/ADN Class	3
ADR/RID/ADN Class	Class 3: Flammable liquid
ADR Label No.	3
IMDG Class	3
ICAO Class/Division	3

Stone Oil

Transport Labels



14.4. Packing group

ADR/RID/ADN Packing group	III
IMDG Packing group	III
ICAO Packing group	III

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant
No.

14.6. Special precautions for user

EMS	F-A, S-F
Emergency Action Code	•3Z
Hazard No. (ADR)	90
Tunnel Restriction Code	(E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments

Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 SI No 716. (CHIP4).

Control of Substances Hazardous to Health Regulations (as amended). (COSHH)

Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007. (CDG 2009)

Management of Health & Safety at Work Regulations 1999.

Approved Code Of Practice

The Control of Substances Hazardous to Health Regulations 2002 (as amended). Approved code of practice and guidance.

Fifth Edition 2005. HSE Books, or download at: <http://www.hse.gov.uk/pubns/priced/l15.pdf>

Guidance Notes

Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

The storage of flammable liquids in containers HSG51 (HSE 1998).

EU Legislation

EC Regulation 1907/2006 (as amended) : 'REACH'.

EC Regulation 1272/2008 (as amended): CLP (Classification, labelling and packaging of substances and mixtures).

ADR (L'Accord européen relative au transport international des marchandises dangereuses par route.)

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Revision Comments

GHS information added.

Change to transport classification.

Revision Date 29-SEP-11 - Rev 01

Revision 01 replaces rev. 00 dated 19-JAN-09

Risk Phrases In Full

R10 Flammable.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Stone Oil

Hazard Statements In Full

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
EUH066	Repeated exposure may cause skin dryness or cracking.
H411	Toxic to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.