

CLEANING SEALING & AFTERCARE

EXTERNAL STONE SEALER TECHNICAL DATA SHEET

REF: 36/5/1 JUNE 18



LTP EXTERNAL STONE SEALER

Environmentally friendly water based impregnating sealer.

Moisture-repellent and stain resistant. Delicately enhances appearance. Helps prevent moss and mould formation. Protects against weathering and efflorescence. UV Resistant and non-yellowing. Breathable. Suitable for use on all types of external masonry including natural and artificial stone, limestone, sandstone, slate, brick and concrete paving.

Directions for use

Preparation:

Ensure surface to be treated is as clean and as dry as possible. If necessary, first wash surfaces down with a dilute solution of LTP Grimex (1:10). Scrub well using a white pad. Rinse well and leave overnight to dry.

Sealing: Shake bottle well before use. Apply evenly to the surface using a foam roller or paint brush. On more absorbent surfaces apply further coats at hourly intervals until the surface is completely saturated. Remove any residual sealer if still visible after one hour.

Coverage (M ² per coat)	1 ltr	5 ltr
Lower porosity surfaces	15m ²	75m ²
Higher porosity surfaces	7.5m ²	37.5m ²

Aftercare

Routinely sweep surfaces to keep them free from organic matter. Surfaces can be washed on a regular basis with LTP Waxwash.

Storage information

Store in a cool, dry, frost-free environment.

Shelf Life – Up to 2 years for un-opened containers.

Other

Dried on over applied sealer can be removed by buffing with a micro-fibre cloth. If dried on residues are left too long and difficult to buff away: apply a little soapy water and gently scrub with a white emulsifying pad, rinse and leave to dry.

Other cont...

On higher porosity surfaces sufficient sealer should be applied until treated surfaces are fully saturated. Do not use in temperatures under 5°C or over 25°C. Clean application tools and brushes with water after use.

Health, Safety & Environmental

**HARMFUL IF INHALED.
HARMFUL TO AQUATIC LIFE WITH LONG
LASTING EFFECTS.**

Keep out of reach of children. Do not breathe fumes/vapours/spray. Use only outdoors or in a well ventilated area. Avoid release into the environment. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell. Dispose of contents/container to hazardous or special waste collection point.

WARNING



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline
+44 (0) 1823 666213 | www.ltp-online.co.uk | info@ltp-online.co.uk
Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN UK

