

CLEANING SEALING & AFTERCARE

PORCELAIN TILE ENHANCER TECHNICAL DATA SHEET

REF: 45/5/1 JANUARY 2025



LTP PORCELAIN TILE ENHANCER

Self-shine enhancer For Porcelain Paving

A low maintenance film forming surface sealer & protector. Enhances and embellishes the appearance. Highly resistant to wear and stains. Facilitates maintenance and cleaning. Leaves surfaces with a 'just washed' look.

Directions for use

For application and cleaning tools see LTP website.

Preparation:

Newly installed surfaces - ensure surface to be treated is completely clean, dry and free from cement and grout stain (see LTP Cement, Grout & Salt Remover).

Existing surfaces - first clean and degrease surfaces with LTP Grimex Intensive Cleaner and rinse well. Leave to dry out thoroughly (24 hrs).

Application:

Clean and dry surface - apply using a foam roller, sealant applicator pad or paint brush. Pour contents into a separate container or dip tray. Apply to the surface without rubbing until an evenly thin film is created. Allow to dry (1 hr). For a more enhanced appearance further coats should be applied at right angles to the first (max.4).

Do not over apply as a heavy layer or too many coats may cause unsightly build up/affect slip resistance and/or reduce the efficiency of the product. Hardens after about an hour but will take a further three days to achieve full hardness and become fully resistant. Always test first to establish the correct method of application and optimum number of coats before general use.

Avoid extremes of temperature. Surface temperature range for application between 5°C - 25°C

Coverage

Approximately 30-40m² per litre (one coat) depending on substrate texture.

Aftercare

Routinely sweep surfaces. Mop regularly using **LTP Porcelain Floor Tile Cleaner**. At some stage, (every 2 – 3 years) complete renovation may be desired. In this case use **LTP Solvex** to strip the original coating before re-applying. Regular cleaning with steam cleaners, jet washers and strong detergents should be avoided.

Storage information

Store in a cool, dry, frost-free environment. Shelf life-Up to 2 years for un-opened containers.

Health, Safety & Environmental

Keep out of reach of children.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Dispose of contents/container in accordance with national



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline

+ 44 (0) 1823 666213 | www.ltp-online.co.uk | technical@ltp-online.co.uk
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN

