

# CLEANING SEALING & AFTERCARE

## SOLVEX TECHNICAL DATA SHEET

REF: 24/5/1



### LTP SOLVEX

#### High Performance Remover. For interior & exterior use.

Removes silicone and acrylic waxes, adhesive polymers, epoxy grout residues and resin residues left by cement free brush in grouts.

For use on stone, travertine, terracotta, slate, sandstone, flagstones, quarry tiles, glazed ceramics and porcelain.

A powerful non-caustic stripper that softens surface residues and waxes, which can then be removed with ease. Suitable for removing most waxes, oil, silicone, acrylic, residual epoxy and resin-based grout.

#### Directions for use

For application and cleaning tools see LTP website.

Pour contents into separate container. Using a roller or paint brush apply generously making sure to work in manageable areas at a time (max 5 – 10 sq.m). Leave for up to 15 minutes. Spray on a small amount of water and scrub using nylon scrubbing pad, short haired stiff bristled scrubbing brush or rotary scrubbing machine. Leave for a further 15 minutes. To release the softened coatings and residues from the surface add a little more water and scrub again. Extract immediately after scrubbing using a sponge or wet vac. During the process do not allow the solution to dry out. If drying should occur apply a light mist of water over the surface to keep it active. If unwanted material remains repeat the process.

If you are unsure of correct application methods, test on an inconspicuous area, prior to general application. If removing residues from epoxy and resin-based grout; apply making sure to avoid a prolonged contact with the joint as well. Non drip viscous solution also suitable for vertical surfaces. In bathrooms protect acrylic surfaces such as baths and shower trays from contact.

To finish and before reapplying waxes or protective coatings wash down surfaces using a dilute solution of LTP Grimex, rinse with plenty of water and leave to dry.

Do not apply during rain or frost or when surface temperatures are below 5°C and above 25°C. Use gloves and protective goggles if there is a risk of direct contact or splashing. Application tools can be cleaned with water.

#### Coverage

Light Stripping 8-10m<sup>2</sup>/litre

Deep Stripping 5m<sup>2</sup>/litre

#### Storage information

Store in a cool, dry, frost-free environment.

Shelf Life – Up to 2 years for unopened containers. Once opened use within 6 months of purchase for optimum results.

### Health, Safety & Environmental

**CONTAINS: Benzyl Alcohol; Silicic Acid, Lithium Magnesium Sodium Salt; (L) C9-11 Pareth-9**

**Causes serious eye irritation.**

**Harmful if swallowed or if inhaled.**

Keep out of reach of children. Do not breathe vapour/spray. Wash contaminated skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in well ventilated area.

**IF SWALLOWED:** Immediately call a POISON CENTRE/doctor. **IF**

**INHALLED:** Remove person to fresh air and keep comfortable for

breathing **IF IN EYES:** Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Dispose of contents/container to a waste collection point in accordance with local regulations.

UFI: DA50-80F8-M008-EUU5



**WARNING**



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline  
+ 44 (0) 1823 666213 | [www.ltp-online.co.uk](http://www.ltp-online.co.uk) | [technical@ltp-online.co.uk](mailto:technical@ltp-online.co.uk)  
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN

2026

