

CLEANING SEALING & AFTERCARE

QUARTZCLEAN TECHNICAL DATA SHEET

REF: 32/Q/.25 MARCH 2020



LTP QUARTZCLEAN

- Intensive cleaner.
- For polished and unpolished quartz.
- Fast acting foaming cleaner.
- Ideal for cleaning and renovating surfaces.
- Removes dirt and grease.

Suitable for internal and external use.

LTP Stoneclean An intensive foaming cleaner that deep cleans surfaces to remove all types of stubborn dirt and grease. Can also be used on laminate and acrylic surfaces.

Directions for use

For application and cleaning tools see LTP website.

Preparation: Areas to be cleaned should be free from dust before application. Mask and protect any surfaces that are not to be cleaned.

Application: Shake can well before use. Hold can 15-20 cm from the surface and spray on evenly using a sweeping motion. Allow the foam to dissolve. Add a little water and agitate with a white pad or similar mild abrasive. Rinse and extract the released residues using a sponge and water. Rub dry using a micro-fibre cloth or similar absorbent towel to finish.

Coverage

Per 250ml : 5 - 10 m² depending upon number of applications required.

Storage information

Store in a cool, dry, frost-free environment.

Notes

Do not spray on to painted or stained surfaces such as cabinets and stained timber skirting boards. Mask and protect these surfaces before application. Use only in open or well ventilated areas. It is recommended that a suitable respiratory mask be worn at all times. Overspray on some surfaces, may in some cases cause damage; in which case wipe up and rinse immediately with clean water. Always test the product on an inconspicuous area for suitability before general application.

Shake can well before use.

Contains : <5% non ionic surfactants, phosphates.
Ingredients: www.ltp-online.co.uk/dr

Health & Safety

Extremely flammable aerosol.
Pressurised container: may burst if heated.

Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing vapour/spray. Use only outdoors or in well ventilated area. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Danger



Use only as directed.



UN 1950



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline
+ 44 (0) 1823 666213 | www.ltp-online.co.uk | technical@ltp-online.co.uk
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN UK

