

CLEANING SEALING & AFTERCARE

SATIN EFFECT FINISHING WAX TECHNICAL DATA SHEET

REF: 02/5/1 June 18



LTP Satin

Water based satin effect finishing wax For interior use

Enhances appearance and further protects surfaces that are pre sealed using an LTP Mattstone or Mattstone H2O. Self polishing or can be polished to restore or increase shine.

Ideal for both treatment and aftercare.

For all types of unpolished natural and artificial stone, encaustics, decorative concrete toppings, vitrified quarry tiles and machine made terracotta.

Directions for use

Preparation:

Ensure surface to be treated is completely clean, dry and free from dirt, grime, cement and grout.

Application:

SHAKE WELL BEFORE USE. Using a cloth or other applicator, apply an even layer of the product onto a clean dry surface. After one hour, apply a second coat at right-angles to the first. The surface is ready to walk on after about 45 minutes. For better sheen, an hour after application, buff with a floor polisher or a lint free cloth to finish.

An initial protection coat of an **LTP Impregnating sealer** is recommended on highly absorbent surfaces such as limestone, sandstone, travertine, concrete toppings and encaustics before application.

Coverage: M² per coat

	1 LTR	5 LTR	25 LTR
Smooth & Honed	30m ²	150m ²	N/A
Textured and Riven	20m ²	100m ²	N/A

Aftercare

Clean surfaces routinely with **LTP WAXWASH**.

Restoring sheen (every 3 months): after cleaning the surface with LTP Waxwash apply **LTP satin** diluting 500ml of product in 5 litres of water: For a greater shine, wait until the surface is dry (after about 1 hour) and buff with a wool cloth or floor polisher.

Renewing protection (once a year): apply undiluted wax with a cloth, fleece pad or other applicator. Buff the surface when it is dry (after about 1 hour)

Keep off of surfaces while they are drying.

Storage information

Store in a cool, dry, frost free environment
Shelf life up to 2 years

Other

Empty containers are recyclable. Active ingredients are water soluble and inert once cured.

Turn off under-floor heating. If in doubt, test on an inconspicuous area prior to general application. Avoid using strong detergents to wash treated surfaces.

Do not use in temperatures under 5°C or over 25°C. Clean application tools with water after use.

Caution: Not recommended for use on outdoor surfaces or in damp environments and where water remains (bathrooms, showers).

Health, Safety & Environmental

Causes serious eye irritation



WARNING

Keep out of reach of children. Wear protective gloves/protective clothing/eye protection. Wash hands thoroughly after handling. # IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Dispose of contents/container to a licensed waste centre in accordance with local/regional/national/international regulations.



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area



For any LTP product information call our technical helpline
+44 (0) 1823 666213 | www.ltp-online.co.uk | info@ltp-online.co.uk
Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN UK

