

CLEANING, SEALING & AFTERCARE

BLACKSTONE SEALER & RESTORER TECHNICAL DATA SHEET

REF: 37/5/1 FEBRUARY 2021



LTP BLACKSTONE SEALER & RESTORER

Water-based Black Impregnating Sealer

For Exterior use

For restoring the appearance of all types of faded dark natural and artificial stone including limestone, marble, slate and concrete pavers.

Directions for use:

Preparation New surfaces: Ensure surface to be treated is as clean and as dry as possible. If necessary, first wash surfaces down with a dilute solution of **LTP Grimex** (1:10). Scrub well using a white pad. Rinse well and leave overnight to dry.

Preparation Older surfaces: Remove blackspot, algae, mildew and stains from detritus use **LTP Blackspot & Algae Remover** Apply to surfaces undiluted and leave for up to 5 hours. Rinse and leave to dry.

Wear gloves and ensure that any surfaces not to be treated are covered and protected.

IMPORTANT: This product is a permanent staining solution that will darken the surface of the stone and the grout joints making it very difficult to remove once applied. Test on an inconspicuous area before general application and do not walk on treated surfaces until the solution has completely dried.

Shake bottle well before use. Apply a small amount to the surface and spread out evenly using a soft cloth or sealant applicator.

Rough cut or textured surfaces apply with foam roller or paint brush. Allow to absorb and dry. Apply further coats (max 3) at 2 hourly intervals until desired depth of colour has been achieved. Leave to dry naturally.

Honed and smooth surfaces: once dry and to ensure even application it may be necessary to work off any excess sealer using a soft cloth. Do not walk on the surface for at least 4 hours after final application.

Allow newly treated surfaces to cure for 24 hours and then rinse with dilute **LTP Powerstripper**, this will help cut back any excess sealer. Before allowing traffic gently rub the surface in a few areas with white cloth or paper towel to make sure that it is colourfast.

Always experiment on a trial area first to establish optimum results.

Coverage M² per coat (approx.)

	250ml	1ltr	5ltr
Lower porosity surfaces	3.75m ²	15m ²	75m ²
Higher porosity surfaces	2m ²	7.5m ²	37.5m ²
Polished surfaces	7.5m ²	30m ²	150m ²

Storage information:

Store in a cool, dry, frost-free environment.
Shelf Life – Up to 2 years for un-opened containers.

Other:

Empty containers are recyclable. Active ingredients are water soluble and inert once cured so therefore not harmful to the environment and ecologically sound. Do not apply when surface temperatures are under 5°C or over 25°C. Clean application tools and brushes with water after use.

Health, Safety & Environmental:

Contains: 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one(2634-33-5).

Keep out of reach of children.



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline
+ 44 (0) 1823 666213 | www.ltp-online.co.uk | technical@ltp-online.co.uk
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN UK

