

CLEANING SEALING & AFTERCARE

GRIMEX SPRAY TECHNICAL DATA SHEET

REF: 7 / .5



LTP GRIMEX SPRAY

Intensive Cleaner

For interior & exterior use

Fast acting formula for cleaning and renovating tiles, worktops, fireplace surrounds and grouting. Does not contain Acid.

Deep cleans surfaces to remove dirt, grease, soot and old layers of wax and sealer. For use on all types of polished and unpolished stone, granite, slate, terracotta, quarry, ceramic, porcelain tiles, concrete and grouting. Suitable for renovating existing surfaces and conditioning new surfaces prior to sealing.

Directions for use

Ensure areas to be treated are dust free prior to application. Spray product directly onto surface and leave for a few minutes. Add a little water and agitate with a brush or suitably mild abrasive pad. Leave for 5-10 minutes and rinse with water. Repeat if necessary. This product should not be used for regular cleaning of sealed surfaces as it will remove the seal. Previously sealed surfaces should be resealed.

Coverage

Coverage per 500ml: 5-10 sq m approx

Storage

Store in a cool, dry, frost-free environment. Shelf life up to 5 years.

Notes:

Important: Test on inconspicuous area before use. Mask and protect painted surfaces, untreated wood and other sensitive areas. Rinse off overspray. Use in well ventilated areas.

Health, Safety & Environmental

Causes skin irritation. Causes serious eye irritation

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Wash hands thoroughly after handling. Wear protective gloves and eye protection. IF ON SKIN: Wash with plenty of water/soap. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. Dispose of contents/container in accordance with local regulations.

WARNING



Contains: <5% non ionic surfactants, phosphates.

Ingredients: www.ltp-online.co.uk/dr

Contains: 2-BUTOXYETHANOL-TETRAPOTASSIUM PYROPHOSPHATE-(L) C9-11 PARETH-9, AMMONIA SOLUTION



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline
+ 44 (0) 1823 666213 | www.ltp-online.co.uk | technical@ltp-online.co.uk
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN UK

