



External Paving & Stone Sealer

Water based impregnating sealer

Exterior use

For all types of natural stone and concrete paving. Suitable for smooth, honed, rough cut and riven surfaces. Delicately enhances colour on some stones. Helps protect against staining. Strongly repels water, oil and grease.

Allows surface to breathe.

Directions for use

Preparation:

SHAKE WELL BEFORE USE.

Always test on an inconspicuous area prior to general use.

Ensure surface to be treated is completely clean, dry and free from dirt, grime, cement and grout. If necessary, first wash surfaces with a dilute solution of Stone & Tile Intensive Cleaner 1:10.

Rinse well to remove residues and leave to dry (24hrs)

Apply generously and evenly using a light pressure sprayer, foam roller or paint brush. On more absorbent surfaces apply further coats at hourly intervals until the surface is fully saturated. Do not use when the surface temperature is under 5°C or over 25°C.

Coverage: M² per coat

	5 LTR
Smooth surfaces	150m ²
Honed surfaces	75m ²
Rough cut and riven surfaces	37.5m ²

Aftercare

Routinely sweep surfaces. Wash periodically with Eco Pro Tec Natural Stone & Porcelain After Care Cleaner.

Storage information

Store in a cool, dry, frost-free environment. Store locked up.

Shelf Life – Up to 2 years for un-opened containers.

Health, Safety & Environmental

Contains: 2-METHYLISOTHIAZOL-3(2H)-ONE

May cause an allergic skin reaction.

Keep out of reach of children.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN: Wash with plenty of water and soap.

If skin irritation or rash occurs: Get medical advice/attention.

WARNING



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area

