

CLEANING, SEALING & AFTERCARE

MPG SEALER H20 TECHNICAL DATA SHEET

REF: 42/5/1.5 JAN 2022



LTP MPG SEALER H20

Water based Impregnating Sealer

Interior & exterior use

For all types of polished marble, polished porcelain and Polished Granite. Natural finish water based impregnating sealer. Provides minimal change to the original appearance. Helps protect against staining. Strongly repels water, oil and grease. Allows surface to breathe.

Directions for use

Preparation: Ensure surface to be treated is completely clean, dry and free from factory nano-wax, dirt, grime, cement and grout. Clean and scrub surfaces thoroughly prior to application using LTP Power Stripper diluted 1:4 with water and scrub surface with a white nylon scrubber. Rinse well to remove residues and leave to dry.

Application: Shake bottle before use. Apply liberally and evenly using a sealant applicator, lint free cloth, lamb's wool applicator or sponge. Leave surfaces to dry. Remove any residual sealer if still visible after one hour by rubbing with a micro fibre cloth or buffing machine. On vertical surfaces apply from the bottom up.

Coverage M² per coat (approx.)

	1ltr	5ltr
Polished surfaces	30m ²	150m ²

Aftercare

Routinely sweep and wash the floor. Clean walls, floors and work surfaces with **LTP Waxwash** or **LTP Stonewash** for stone surfaces or **LTP Porcelain Floor Tile Cleaner** for porcelain.

Other

Dried on over applied sealer can be removed by rubbing with a micro fibre cloth or rotary machine and polishing bonnet. If dried on residues are left too long and difficult to remove use warm soapy water and gently scrub with a white nylon scrubber, rinse and leave to dry. Empty containers are recyclable. Active ingredients are water soluble and inert once cured. Turn off under-floor heating prior to sealing. If in doubt, test on an inconspicuous area prior to general application. Avoid using strong detergents to wash treated surfaces. On higher porosity materials sufficient sealer should be applied until treated surfaces are fully saturated. Do not use in temperatures under 5°C or over 25°C. Clean application tools and brushes with water after use. Dispose of contents/container to a licensed waste centre in accordance with local/regional /national/international regulations.

Storage information

Store in a cool, dry, frost-free environment. Shelf Life – Up to 2 years for un-opened containers.

Health, Safety & Environmental

Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one(2634-33-5)

Keep out of reach of children.



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline

+ 44 (0) 1823 666213 | www.ltp-online.co.uk | technical@ltp-online.co.uk
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN

