

CLEANING, SEALING & AFTERCARE

COLOUR INTENSIFIER & STAINBLOCK H2O TECHNICAL DATA SHEET

REF: 42/5/1/5 JAN 2022



LTP COLOUR INTENSIFIER & STAINBLOCK H2O

Water based Impregnating Sealer

Interior & exterior use

For all types of natural and artificial stone, quarry, brick, concrete and paving. Honed, rough cut and polished surfaces. Colour enhancing water based impregnating sealer. Provides an enhanced natural finish. Helps protect against staining. Strongly repels water, oil and grease. Allows surface to breathe. Helps reduce efflorescence.

Directions for use:

Preparation: Ensure surface to be treated is completely clean, dry and free from dirt, grime, cement and grout. If necessary, first wash surfaces with a dilute solution of **LTP Grimex** 1:10 and white nylon scrubber. Rinse well to remove residues and leave to dry (24hrs).

Rough cut, tumbled, textured or riven surfaces: Shake bottle before use. Apply generously and evenly using foam roller or paint brush. On more absorbent surfaces apply further coats at hourly intervals until the surface is fully saturated.

Honed, smooth and polished surfaces: Shake bottle before use. Apply liberally and evenly using a sealant applicator, lint free cloth, lamb's wool applicator or sponge. Leave surfaces to dry. Remove any residual sealer if still visible after one hour by rubbing the surface with a microfibre cloth. On larger surface areas machines can be used. On vertical surfaces apply from the bottom up.

Coverage M² per coat (approx.)

	1ltr	5ltr
Lower porosity surfaces	15m ²	75m ²
Higher porosity surfaces	7.5m ²	37.5m ²
Polished surfaces	30m ²	150m ²

Aftercare:

Routinely sweep and wash the floor.
Clean floors with **LTP Waxwash** and walls and work surfaces with **LTP Stonewash**.

Other:

Over applied sealer can be removed by rubbing with micro fibre cloth or rotary machine polishing bonnet. If sealer residues are left too long and difficult to remove, use warm soapy water and gently scrub with a white nylon scrubber, rinse and leave to dry. Empty containers are recyclable. Active ingredients are water soluble and inert once cured. Turn off under-floor heating prior to sealing. If in doubt, test on an inconspicuous area prior to general application. Avoid using strong detergents to wash treated surfaces. On higher porosity materials sufficient sealer should be applied until treated surfaces are fully saturated. Do not use in temperatures under 5°C or over 25°C. Clean application tools and brushes with water after use.

Storage information:

Store in a cool, dry, frost-free environment. Shelf Life – Up to 2 years for un-opened containers.

Health, Safety & Environmental:

Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one(2634-33-5).

Keep out of reach of children. Dispose of contents/container to a licensed waste centre in accordance with local/regional /national/international regulations.



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline

+ 44 (0) 1823 666213 | www.ltp-online.co.uk | technical@ltp-online.co.uk
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN

