

CLEANING SEALING & AFTERCARE

GROUT STAIN REMOVER TECHNICAL DATA SHEET

REF: 8/5/1 FEBRUARY 2023



LTP GROUT STAIN REMOVER

Cement, Limescale & Grout Residue Remover

Interior & exterior use

A rapid action cleaning agent for removing cement residues, grout stain, efflorescence and other similar deposits. Use in dilute or concentrated form.

For glazed and un-glazed ceramics, slate, quarry tiles, brick, terracotta & acid resistant natural stones.

Directions for use:

In mild cases and on absorbent tiles:

Dilute 1 part Grout Stain Remover in 4 parts cold water. Apply with a cloth or sponge wrung out in the solution. Wipe off thoroughly with a clean damp cloth.

In more severe cases:

Dilute 1 part Grout Stain Remover in 1 part cold water. Apply liberally and spread over surface of tiles. If necessary, agitate with a nylon scrubber and leave to react for five minutes, keeping wet with additional Grout Stain Remover solution. Mop up and rinse thoroughly with clean cold water.

In extremely severe cases:

Use undiluted and agitate with a nylon scrubber or mechanical scrubber if necessary. Neutralise treated surface with clean cold water after use.

N.B. Always rinse surfaces thoroughly with clean cold water.

Coverage M² per application (approx.)

	1ltr	5ltr
Mild cases	30m ²	150m ²
More severe cases	10m ²	50m ²
Extremely severe	5m ²	25m ²

Storage information:

Store in a cool, dry, frost-free environment. Shelf Life – Up to 5 years

Other:

Not suitable for use on surfaces that are calcareous, sensitive to acids (e.g. stainless steel, chrome, enamel etc), or contain lime (i.e. marble, travertine, limestone, engineered stone & sandstone containing iron). In conditions of extreme humidity LTP Grout Stain Remover vapour may react with acid sensitive surfaces. Any contaminated surface should be rinsed off immediately with plenty of **clean cold water**. Do not use when under floor heating systems are in operation. **Important:** - Always test the solution on a small inconspicuous area prior to general application. Work in manageable sized areas. Prolonged contact with grout joints should be avoided.

Health, Safety & Environmental:

Contains Hydrochloric Acid <10%.

Causes skin irritation. Causes serious eye irritation.

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Wash hands thoroughly after handling. Wear protective gloves, protective clothing, eye protection. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Dispose of contents/container to a licensed waste centre in accordance with local/regional /national/international regulations.

Label in Accordance With (EC) No 1272/2008



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline
+ 44 (0) 1823 666213 | www.ltp-online.co.uk | technical@ltp-online.co.uk
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN

