

# CLEANING SEALING & AFTERCARE

## FULLERS EARTH TECHNICAL DATA SHEET

REF: 18 MARCH 2017



### LTP FULLERS EARTH

#### Stain Remover

#### Suitable for Interior & Exterior use

For use on all types stone, marble, terracotta, concrete, external paving, wood, fabrics and leather.

Ultra-absorbent stain remover for all greasy stains (oil, grease, make-up, sebum). For use on stone, marble, terracotta, concrete, external paving, wood, fabrics and leather.

#### Directions for use

For application and cleaning tools see LTP website.

#### On fabrics, leather, rugs, carpets, wood (recent stains)

Sponge the stain as much as possible with a clean cloth without rubbing, going from the outside to the middle of the stain.

Shake the container well and powder the stain with the fuller's earth. Leave for at least 30 minutes then delicately brush. Apply again if necessary.

#### On stone, marble, terracotta, concrete and external paving combine with LTP Spot Stain Remover to remove ingrained oil stains from porous surfaces.

Apply directly onto the stain making sure to spread the solution out to the edge of the tile up to the grout joints and leave to absorb into the surface for about 5 – 10 minutes. Powder the stain with the 'LTP Fuller's Earth'. Wet the powder again with the LTP Spot Stain Remover and then cover it once more with the Fuller's Earth. Leave for 24 hours. Brush away the powder and wash with a dilute solution of LTP Grimex. Rinse well with a sponge and water and leave to thoroughly dry before re-sealing. For stubborn stains renew the application as many times as necessary.

#### Notes

On delicate surfaces, first make a test on a hidden area.

#### Storage information

Store in a cool, dry, frost-free environment.

#### Health, Safety & Environmental

Attention:  
Keep out of the reach of children.  
Use only in well ventilated areas.  
Do not breathe dust.  
Use as directed only.



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline  
+ 44 (0) 1823 666213 | [www.ltp-online.co.uk](http://www.ltp-online.co.uk) | [technical@ltp-online.co.uk](mailto:technical@ltp-online.co.uk)  
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN UK

