

# CLEANING SEALING & AFTERCARE

## STONECLEAN TECHNICAL DATA SHEET

REF: 32/25 MAY 2021



### LTP STONECLEAN

- **Intensive cleaner.**
- **For polished and unpolished stone.**
- **Fast acting foaming cleaner.**
- **Ideal for cleaning and renovating stone fireplaces and worktops.**
- **Removes dirt and grease.**

**Suitable for internal and external use.**

**LTP Stoneclean** is an intensive foaming cleaner that deep cleans surfaces to remove all types of dirt and grease. Ideal for removing the build up of wax and aftercare product. Use as an intensive cleaner for conditioning new surfaces before sealing or as an intensive cleaner for renovating existing surfaces. Suitable for polished and unpolished natural and artificial stone including limestone, granite, marble, travertine, slate, sandstone, quartz, terrazzo, basalt, concrete and all other types of masonry surface. Can also be used on laminate and acrylic worktops.

### Directions for use

For application and cleaning tools see LTP website.

#### Preparation:

Areas to be treated must be free from dust before application. Mask and protect surfaces that are not to be treated.

**Honed, smooth, polished, rough cut, tumbled, textured or riven surfaces:** Shake well. Hold can 15 to 20cm from the surface and spray in a sweeping motion. Allow the foam to dissolve. This will take 5 to 10 minutes. Add a little water and agitate with a white emulsifying pad or similar mild abrasive pad, cloth or brush to help release the ground in dirt and grime. Rinse well with plenty of water and a sponge making sure to change rinsing water regularly. On extremely dirty surfaces this process may need to be repeated.

### Coverage

**Per 250ml :** 5 - 10 m<sup>2</sup> depending upon the porosity and the number of coats required.

### Storage information

Store in a cool, dry, frost-free environment.

### Notes

Do not spray on to painted or stained surfaces such as cabinets and stained timber skirting boards. Mask and protect these surfaces before application. Use only in open or well ventilated areas. It is recommended that a suitable respiratory mask be worn at all times. Overspray on some surfaces, may in some cases cause damage; in which case wipe up and rinse immediately with clean water. Always test the product on an inconspicuous area for suitability before general application.

**Shake can well before use.**

**Contains :** <5% non ionic surfactants, phosphates.  
**Ingredients:** [www.ltp-online.co.uk/dr](http://www.ltp-online.co.uk/dr)

### Health & Safety

**Extremely flammable aerosol.**

**Pressurised container: may burst if heated.**

**Causes skin irritation. Causes serious eye irritation**

Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wear protective gloves, eye protection, protective clothing. **IF ON SKIN:** Wash with plenty of soap and water. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Protect from sunlight. Do not expose to temperatures exceeding 50°C. Dispose of contents and container to a hazardous or special waste collection point.

### Danger



**Use only as directed.**

**UN 1950**

**335** ➤



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline  
+ 44 (0) 1823 666213 | [www.ltp-online.co.uk](http://www.ltp-online.co.uk) | [technical@ltp-online.co.uk](mailto:technical@ltp-online.co.uk)  
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN UK

