

# CLEANING SEALING & AFTERCARE

## WALL & FLOOR GROUT PROTECTOR TECHNICAL DATA SHEET

REF: 15/1 MARCH 2017



### LTP GROUT PROTECTOR

**Impregnating Sealer for porous grout joints.**

**For interior use.**

Suitable for kitchen and bathroom walls and floors: protects against water, dirt, grease, mould and limescale.

Forms a clear, colourless barrier. Helps protect absorbent, porous grout joints.

### Directions for use

**For application and cleaning tools see LTP website.**

**Important:** LTP Wall and Floor Grout Protector is intended for use only on porous grout joints between non-porous glazed or highly vitrified ceramic tiles (not epoxy grout).

Ensure that the grout surface to be treated is completely clean and dry. Allow grout to dry for 24 hours after cleaning. Apply a generous coat of LTP Grout Protector using a small paintbrush and allow to soak in. To avoid leaving a film on the adjoining tiles, wipe away any surplus as you go with a clean, fluff-free cloth, dampened, if necessary, with a little white spirit. Do not treat more than an area of 2 or 3 square metres at a time to ensure that all of the product is absorbed into the grout. Remove any excess LTP Grout Protector which is not absorbed into grout joints within 20 minutes of application. Repeat process after one hour. If necessary, further treatments can be applied after an hour or so. After 48 hours the surface can be cleaned as normal. Use a dry cloth to wipe away any excess from non-absorbent surfaces.

**Use only in well ventilated areas. Do not breathe vapours.**

### Coverage

Up to 500 linear metres per 1 litre

### Aftercare

If necessary, wipe over grout joints using a mild detergent. Use LTP Grimex to remove stubborn surface marks, in which case you may need to re-seal treated areas.

### Notes

**Please Note:**

Protect glass, sanitary ware, polished surfaces, plastics, painted and other sensitive surfaces against splashes. Do not allow excess to dry on the surface. Wipe away carefully. If in doubt, test the product on a small area. Do not use in direct sunlight or in temperatures over 25 degrees C.

Drying Time: Approx 30-40 minutes. Becomes fully effective after approx 48 hours.

### Storage information

Store in a cool, dry, frost free environment.

Shelf Life – Up to 4 years for un-opened containers.

### Health, Safety & Environmental

**Contains: Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), Hydrocarbons, C9, aromatics**

**Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.**

Keep out of the reach of children. IF SWALLOWED: immediately call a POISON CENTRE or doctor/physician-Do NOT induce vomiting. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe fume, vapours, mist, spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear eye protection, protective gloves. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Dispose of contents/container in accordance with local/national regulations. Repeated exposure may cause skin dryness or cracking.



### VOC STATEMENT

EU Limit value for this product (Cat A/h) 750g/L (2010)  
This product contains max 749g/L VOC

UN 1300

EC Label.EC No 1272/2008



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline  
+ 44 (0) 1823 666213 | [www.ltp-online.co.uk](http://www.ltp-online.co.uk) | [technical@ltp-online.co.uk](mailto:technical@ltp-online.co.uk)  
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN UK

