

# CLEANING SEALING & AFTERCARE

## STONE OIL IMPREGNATING SEALER TECHNICAL DATA SHEET

REF: 26/5/1/5/25 MARCH 2017



### LTP STONE OIL

**Oil Based Impregnating Sealer  
For Interior & Exterior use  
For travertine, limestone, sandstone, slate,  
marble, porcelain, granite, terracotta, quarry  
tiles, brick and external paving.**

Easy to apply oil based impregnating sealer ideal for low porosity slate, stone & terracotta.  
Strongly enhances the appearance

#### Directions for use

For application and cleaning tools see LTP website.

Shake well.

Surfaces should be completely clean & dry .  
Apply sparingly using a soft cloth, paint brush or sealant applicator pad to the surface. Remove unabsorbed excess within 1 hour. Porous surfaces may require more than one application. Leave to cure for a minimum of 24 hours before allowing traffic. Keep as dry as possible for the first 3 days. External surfaces: no further treatment necessary. Internal surfaces: can be finished with LTP Colour Intensifier or LTP Clear or Antique Wax or LTP Ironwax Satin or Gloss.

Important: Used cloths should be burnt as they may spontaneously combust. Allow good ventilation during application. Avoid working in direct sunlight; rapid oxidization may inhibit effectiveness. Excess sealer that is left to dry on the surface can be removed with white spirit

#### Coverage

Lower porosity floors (250ml per 5 sqm) per 10 sq m  
approximately 1 litre

Medium porosity floors (250ml per 2 sq m) per 10 sq m  
approximately 2 litres

#### Aftercare

Interior surfaces finished with LTP Ironwax Satin or Gloss, use LTP Floorshine . Surfaces finished with LTP Stone Oil, Colour Intensifier, Clear or Antique wax use LTP Waxwash.

#### Storage information

Store in a cool, dry, frost-free environment.

Shelf Life – Up to 4 years for un-opened containers.

### Health, Safety & Environmental

**Contains: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics.  
May be fatal if swallowed and enters airways.  
Repeated exposure may cause skin dryness or cracking.**

If medical advice is needed, have product container or label at hand. Keep out of reach of children. IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Do NOT induce vomiting. Store locked up. Dispose of contents/container in accordance with local authority requirements.

EC Label EC No 1272/2008



**Danger**

#### VOC STATEMENT

EU Limit value for this product  
(Cat A/h) 750g/L (2010)

This product contains max 391g/L VOC



This information is offered without guarantee.

The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline  
+ 44 (0) 1823 666213 | [www.ltp-online.co.uk](http://www.ltp-online.co.uk) | [technical@ltp-online.co.uk](mailto:technical@ltp-online.co.uk)  
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN UK

