

# CLEANING SEALING & AFTERCARE

## ANTIQUÉ WAX TECHNICAL DATA SHEET

REF: 3/2/1 MARCH 2017



### LTP ANTIQUÉ WAX

#### A medium brown wall and floor tile polish

For use on travertine, slate, limestone, sandstone, tumbled marble, flamed and rough cut granite, terracotta, quarry and brick. Provides an aged appearance.

A soft paste wax, blended from three types of wax giving surfaces an excellent shine. Provides a resilient protective layer against water, dust, dirt and other commonly found household contaminants.

LTP Antique Wax comes ready to use and is easily applied by cloth before polishing to a finish. Suitable for use on travertine, limestone, sandstone, slate, tumbled marble, flamed and rough cut granite, terracotta, quarry and brick.

#### Directions for use

For application and cleaning tools see LTP website.

The surface to be treated should be completely, clean, dry and any pre-polish sealer thoroughly cured. Stir well. Apply sparingly with a soft fluff-free cloth ensuring that the area of application is manageable. Quickly buff wax to a shine using a short haired brush, soft cloth or mechanical polisher.

**Please Note:** When using LTP Antique Wax on higher absorbency floors, the wax may be absorbed into the surface unevenly, consequently proving difficult to shine. Therefore, when treating such floors, it may be necessary to reduce the absorbency by pre-applying a suitable impregnating sealer. LTP Antique Wax can be applied to surfaces that have been impregnated with LTP Boiled Linseed Oil, Stone Oil, Mattstone and Colour Intensifier. The type of impregnator used will depend on the type of material that is being sealed.

#### Coverage

On most floors, 1 litre /10 square metres (two coats).

#### Storage information

Store in a cool, dry, frost-free environment.

Shelf life-Up to 2 years

#### Aftercare

Wash with LTP Waxwash. Ensure that areas where the seal has been worn or damaged are re-waxed. Apply a fresh coat of LTP Antique Wax to your floor should it begin to show signs of stain absorption. This should be done after the surface has been washed and allowed to thoroughly dry.

NB. Test the wax on an inconspicuous area prior to general application. LTP Antique Wax may not properly harden if too much polish is applied or if applied to surfaces containing moisture. In either case it may be difficult to obtain a shine. It will not polish properly if used on partially cured sealers or if the floor has not been properly pre-sealed. This product may be less ably applied in cold weather, in which case it may help to warm the can in tepid water (N.B. Do not use naked flame).

#### Health, Safety & Environmental

**CONTAINS: Hydrocarbons C7-C9 n-alkanes, Isoalkanes, Cyclics. Repeated exposure may cause skin dryness or cracking. Flammable solid. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.**

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Use only outdoors or in a well ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed – immediately call a poison centre or doctor/physician. If inhaled – remove victim to fresh air and keep at rest in a position comfortable for breathing. If in eyes – rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Do NOT induce vomiting. Store in a well-ventilated place. Store locked up. Dispose of this material and its container to hazardous or special waste collection point.

UN 1263



**DANGER**

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline  
+ 44 (0) 1823 666213 | [www.ltp-online.co.uk](http://www.ltp-online.co.uk) | [technical@ltp-online.co.uk](mailto:technical@ltp-online.co.uk)  
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN UK

