

CLEANING SEALING & AFTERCARE

CLEAR WAX TECHNICAL DATA SHEET

REF: 4/2/1 February 2022



LTP CLEAR WAX

A clear finish wall and floor tile polish.

For use on travertine, limestone, sandstone, slate, tumbled marble, flamed granite, terracotta, quarry, brick and wood.

A soft paste blended from three types of wax giving surfaces an excellent shine. Provides a resilient protective layer against water, dust, dirt and other commonly found household contaminants. LTP Clear Wax is easily applied by cloth before polishing to a finish. Suitable for use on travertine, limestone, sandstone, slate, tumbled marble, flamed granite, terracotta, quarry, brick and wood.

Directions for use

For application and cleaning tools see LTP website. The surface to be treated should be completely, clean, dry and any pre-polish sealer thoroughly cured. Stir well. Apply sparingly with a soft fluff-free cloth ensuring that the area of application is manageable. Quickly buff wax to a shine using a short haired brush, soft cloth or mechanical polisher.

Please Note: When using LTP Clear Wax on higher absorbency floors, the wax may be absorbed into the surface unevenly, consequently proving difficult to shine. Therefore, when treating such floors, it may be necessary to reduce the absorbency by pre-applying a suitable impregnating sealer. LTP Clear Wax can be applied to surfaces that have been impregnated with LTP Boiled Linseed Oil, Stone Oil, Mattstone and Colour Intensifier. The type of impregnator used will depend on the type of material that is being sealed.

Coverage

On most floors, 1 litre /10 square metres (two coats).

Storage information

Store in a cool, dry, frost-free environment.

Shelf life - Up to 2 years.

Aftercare

Aftercare Wash with LTP Waxwash. Ensure that areas where the seal has been worn or damaged are re-waxed. Apply a fresh coat of LTP Clear Wax to your floor should it begin to show signs of stain absorption. This should be done after the surface has been washed and allowed to thoroughly dry.

NB. Fully hardened LTP Clear Wax may sometimes dry slightly opaque (slightly white), especially if it is over applied or not correctly buffed. This whiteness may show up more on darker, rougher tiles. Therefore, it is advisable to test the wax on an inconspicuous area prior to general application. LTP Clear Wax may not properly harden if too much polish is applied or if applied to surfaces containing moisture. In either case it may be difficult to obtain a shine. It will not polish properly if used on partially cured sealers or if the floor has not been properly pre-sealed. This product may be less ably applied in cold weather, in which case it may help to warm the can in tepid water (N.B. Do not use naked flame).

Health, Safety & Environmental

Flammable solid. Toxic to aquatic life with long lasting effects. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure.

Keep away from heat/sparks/open flames/hot surfaces. No smoking. If medical advise is needed, have product container or label at hand. Keep out of reach of children. Use only outdoors or in well-ventilated area. Avoid release to the environment. Dispose of contents in accordance with local, state or national legislation.

UN1263



DANGER

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline

+44 (0) 1823 666213 | www.ltp-online.co.uk | technical@ltp-online.co.uk
Tort East, Milverton Road, Wellington, Somerset, TA21 0AN UK

