

CLEANING, SEALING & AFTERCARE

GLAZE PROTECTOR TECHNICAL DATA SHEET

REF: LTP/20



LTP GLAZE PROTECTOR

Self Shine Sealer

For Non Porous Surfaces

INTERIOR USE ONLY

(Not wet rooms or shower enclosures)

Retains the 'just washed' look on glazed ceramic, porcelain, unpolished porcelain and vitrified quarry tiles. Easy to maintain.

Low maintenance film forming sealer. Protects and embellishes the surface. Highly resistant to wear and stains. Facilitates maintenance and cleaning. Leaves surfaces with a 'just washed' look

Directions for use

For application and cleaning tools see LTP website. **Newly installed surfaces** - ensure surface to be treated is completely clean, dry and free from cement and grout stain (see **LTP Grout Stain Remover**).

Existing surfaces - first clean and degrease surfaces with **LTP Grimex** and rinse well. Leave to dry out thoroughly (24 hrs). Any retained moisture in the grout joints may cause the **LTP Glaze Protector** to dry opaque or prevent the seal from reaching full hardness.

Application:

Apply using a J cloth or sealant applicator pad. Pour contents into a separate container. Dip cloth into the solution and wring out. Apply evenly to the surface without rubbing. Apply until an evenly thin film is created (Avg. 3 times). Allow to dry (1 hr). For a glossier finish further coats should be applied at right angles to the first (max.6).

Do not over apply as too many coats may cause unsightly build up and/or reduce the efficiency of the product. Hardens after about an hour but will take a further three days to achieve full hardness and become fully water resistant. Always test first to establish the correct method of application and optimum number of coats before general use.

Avoid extremes of temperature. Do not apply on to rubber floors.

Coverage

Approximately 30-40m² per litre (one coat) depending on substrate porosity.

Aftercare

Routinely sweep the floor. Use **LTP Floorshine** to clean and protect treated surfaces. In areas where the seal becomes worn, apply more **LTP Glaze Protector**. At some stage, complete renovation of the seal may be desired. In this case use **LTP Grimex** to strip the original seal before re-sealing. Avoid using strong detergents to wash surfaces treated with LTP Glaze Protector.

Storage information

Store in a cool, dry, frost-free environment.

Shelf life-Up to 4 years for un-opened containers.

Health, Safety & Environmental

Contains: 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one; 2-methylisothiazol-3(2H)-one; Tetraamminezinc(2+) carbonate; Reaction mass 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

May cause an allergic skin reaction.

Causes serious eye irritation.

Harmful to aquatic life with long lasting effects.

Keep out of reach of children. If medical advice is needed, have product container or label at hand. Avoid breathing vapours, spray. Wear eye protection, protective gloves, protective clothing. Specific treatment (see supplemental first aid instruction on this label). Dispose of contents and container to a hazardous or special waste collection point. UFI: HU80-00RJ-500J-JUQT



WARNING

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline

+ 44 (0) 1823 666213 | www.ltp-online.co.uk | technical@ltp-online.co.uk
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN

