

# CLEANING SEALING & AFTERCARE

## STONECARE AFTERCARE CLEANER TECHNICAL DATA SHEET

REF: 30/25 MARCH 2017



### LTP STONECARE

- **Aftercare cleaner.**
- **For polished and unpolished stone.**
- **Gentle cleaner ideal for stone fireplaces and worktops.**
- **Cleans and embellishes delicate surfaces**

#### Suitable for internal and external use

**LTP Stonecare** low foaming maintenance cleaner is a gentle, neutral product that cleans without damaging even the most delicate surfaces. Suitable for polished and unpolished natural and artificial stone including limestone, granite, marble, travertine, slate, sandstone, quartz, terrazzo, basalt, concrete and all other types of masonry surface. Can also be used on laminate and acrylic worktops. Fresh clean fragrance.

#### Directions for use

For application and cleaning tools see LTP website.

**Rough cut, tumbled, textured or riven surfaces:**  
Shake well. Hold 20cm from surface and spray. Wipe over with a clean dry cloth and leave to dry.

**Honed, smooth and polished surfaces**  
Use as above, but finish by buffing with a clean dry cloth.

**Shake can well before use.**

#### Notes:

**NB.** Always test the product on an inconspicuous area for suitability before general application.

**Contains:** <5% Anionic surfactants.  
< 5% Non-ionic surfactants.  
Perfume

**Ingredients:** [www.ltp-online.co.uk/dr](http://www.ltp-online.co.uk/dr)

#### Storage information


Store in a cool, dry, frost-free environment.

### Health & Safety

**Extremely flammable aerosol.**

**Pressurised container: may burst if heated.**

Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing vapour/spray. Use only outdoors or in well ventilated area. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.



### Danger

Use only as directed



UN 1950



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline  
+44 (0) 1823 666213 | [www.ltp-online.co.uk](http://www.ltp-online.co.uk) | [info@ltp-online.co.uk](mailto:info@ltp-online.co.uk)  
Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN UK

