



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Name : Grout Protector
 Product code : LTP/13

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public : Yes with guidance
 Main use category : Consumer use, Professional use, Industrial use
 Use of the substance/mixture : Colour enhancing tile sealer

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

AM Robb Ltd (T/A LTP)
 Tone Estate,
 Milverton Road,
 Wellington,
 Somerset,
 TA21 0AN

Tel: +44 (0) 1823 666213 Office hours only 8.30am–5.30pm Mon–Fri
 Fax: +44 (0) 1823 665685
 Email: info@ltp-online.co.uk

1.4. Emergency telephone number

Emergency number : +44 (0) 1270 502891 (Out of Office Hours Emergency Number)

Country	Organisation/Company	Address	Emergency number
IRELAND (REPUBLIC OF)	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	: +353 1 8379964
UNITED KINGDOM	National Poisons Information Service (NHS Direct)	http://www.npis.org	111 (England & Wales only) or 112 (EU) or 08454 24 24 24 (Scotland)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3 H226
 STOT SE 3 H335
 STOT SE 3 H336
 STOT RE 1 H372
 Asp. Tox. 1 H304
 Aquatic Chronic 2 H411

Full text of H-statements: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Xn; R65
 Xn; R48/20
 Xi; R37
 N; R51/53
 R10
 R66
 R67

Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available





TILE AND STONE SURFACE PROTECTION

LTP GROUT PROTECTOR

CLEANING, SEALING AND AFTERCARE SOLUTIONS

according to Regulation (EC) No. 453/2010 Date of issue: 24/06/2015 Revision date: 06/07/2015

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazardous ingredients :

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), hydrocarbons, C9, aromatics

Hazard statements (CLP) :

H226 - Flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H372 - Causes damage to organs through prolonged or repeated exposure
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (CLP) :

P102 - Keep out of reach of children
P301+P310 + P331- IF SWALLOWED: immediately call a POISON CENTER or doctor/physician - Do NOT induce vomiting
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P260 - Do not breathe fume, vapours, mist, spray
P264 - Wash hands thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area
P273 - Avoid release to the environment
P280 - Wear eye protection, protective gloves
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P501 - Dispose of contents/container in accordance with local/national regulations

EUH phrases :

EUH066 - Repeated exposure may cause skin dryness or cracking

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	(CAS No) 64742-82-1. (EC no) 919-446-0 (REACH-no) 01-2119458049-33-XXXX	50 - 80	R10 Xn; R65 R66 N; R51/53 Xn; R48/20
hydrocarbons, C9, aromatics	(CAS No) 64742-95-6. (EC no) 918-668-5 (REACH-no) 01-2119455851-35-XXXX	5 - 30	R10 Xi; R37 Xn; R65 R66 R67 N; R51/53
naphtha (petroleum), hydrotreated heavy (contains less than 0,1 % w/w benzene) substance with a Community workplace exposure limit substance with national workplace exposure limit(s) (PL)	(CAS No) 64742-48-9 (EC no) 265-150-3 (EC index no) 649-327-00-6	0,1 - 1	Xn; R65 R66 R10
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	(CAS No) 64742-82-1. (EC no) 919-446-0 (REACH-no) 01-2119458049-33-XXXX	50 - 80	Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

2 of 8



TONE ESTATE, MILVERTON ROAD, WELLINGTON SOMERSET, TA21 0AN

TEL:01823 666213

FAX:01823 665685

Email: info@ltp-online.co.uk

Technical Email:technical@ltp-online.co.uk

www.ltp-online.co.uk





TILE AND STONE SURFACE PROTECTION

LTP GROUT PROTECTOR

CLEANING, SEALING AND AFTERCARE SOLUTIONS

according to Regulation (EC) No. 453/2010 Date of issue: 24/06/2015 Revision date: 06/07/2015

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
hydrocarbons, C9, aromatics	(CAS No) 64742-95-6. (EC no) 918-668-5 (REACH-no) 01-2119455851-35-XXXX	5 - 30	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
naphtha (petroleum), hydrotreated heavy (contains less than 0,1 % w/w benzene) substance with a Community workplace exposure limit substance with national workplace exposure limit(s) (PL)	(CAS No) 64742-48-9 (EC no) 265-150-3 (EC index no) 649-327-00-6	0,1 - 1	Asp. Tox. 1, H304

Full text of R- and H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
- First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Repeated exposure may cause skin dryness or cracking.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Causes damage to organs through prolonged or repeated exposure.
- Symptoms/injuries after inhalation : May cause respiratory irritation. May cause drowsiness or dizziness.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapour.
- Explosion hazard : May form flammable/explosive vapour-air mixture.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection. Avoid breathing fume, vapours.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if substance enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

3 of 8



TONE ESTATE, MILVERTON ROAD, WELLINGTON SOMERSET, TA21 0AN

TEL:01823 666213

FAX:01823 665685

Email: info@ltp-online.co.uk

Technical Email:technical@ltp-online.co.uk

www.ltp-online.co.uk





TILE AND STONE SURFACE PROTECTION

LTP GROUT PROTECTOR

CLEANING, SEALING AND AFTERCARE SOLUTIONS

according to Regulation (EC) No. 453/2010 Date of issue: 24/06/2015 Revision date: 06/07/2015

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.
- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No open flames. No smoking. Use only non-sparking tools. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so. Use only outdoors or in a well-ventilated area. Do not breathe fume, vapours, mist, spray. Take precautionary measures against static discharge. Avoid breathing fume, Vapours.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash Skin thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof Flame proof, lighting, electrical equipment and ventilation equipment.
- Storage conditions : Keep container tightly closed. Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, Heat and ignition sources.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

naphtha (petroleum), hydrotreated heavy (contains less than 0,1 % w/w benzene) (64742-48-9)		
EU	IOELV TWA (mg/m ³)	1000 mg/m ³ 8h
Switzerland	VLE (mg/m ³)	600 mg/m ³
Switzerland	VLE (ppm)	100 ppm
Switzerland	VME (mg/m ³)	300 mg/m ³
Switzerland	VME (ppm)	50 ppm
Switzerland	Remark (CH)	4x15*
Poland	NDS (mg/m ³)	300 mg/m ³
Poland	NDSch (mg/m ³)	900 mg/m ³

8.2. Exposure controls

- Appropriate engineering controls : Provide adequate general and local exhaust ventilation.
- Personal protective equipment : Protective goggles. Gloves.



- Hand protection : Wear protective gloves.
- Eye protection : Chemical goggles or safety glasses.
- Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
- Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Colourless liquid.
- Colour : clear.
- Odour : Hydrocarbon.
- Odour threshold : No data available
- pH : No data available





TILE AND STONE SURFACE PROTECTION

LTP GROUT PROTECTOR

CLEANING, SEALING AND AFTERCARE SOLUTIONS

according to Regulation (EC) No. 453/2010 Date of issue: 24/06/2015 Revision date: 06/07/2015

Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 150 - 200 °C
Flash point	: ≥ 40 °C
Auto-ignition temperature	: 230 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable liquid and vapour
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0,785 g/cm ³
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: 0,85 cSt 25°C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified Repeated exposure may cause skin dryness or cracking
Serious eye damage/irritation	: Not classified Based on available data, the classification criteria are not met
Respiratory or skin sensitisation	: Not classified Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: May cause respiratory irritation. May cause drowsiness or dizziness.





TILE AND STONE SURFACE PROTECTION

LTP GROUT PROTECTOR

CLEANING, SEALING AND AFTERCARE SOLUTIONS

according to Regulation (EC) No. 453/2010 Date of issue: 24/06/2015 Revision date: 06/07/2015

Specific target organ toxicity (repeated exposure) : Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Toxic to aquatic life with long lasting effects.

naphtha (petroleum), hydrotreated heavy (contains less than 0,1 % w/w benzene) (64742-48-9)	
LC50 fish 1	> 1000 mg/l (Pisces)
EC50 Daphnia 1	> 1000 mg/l (Daphnia magna)
LC50 fish 2	> 100 mg/l (Pisces)
EC50 Daphnia 2	> 100 mg/l (Crustacea)
Threshold limit algae 1	> 1000 mg/l (Algae)
Threshold limit algae 2	> 100 mg/l (Algae)

12.2. Persistence and degradability

Colour Intensifier	
Persistence and degradability	May cause long-term adverse effects in the environment.
naphtha (petroleum), hydrotreated heavy (contains less than 0,1 % w/w benzene) (64742-48-9)	
Persistence and degradability	Readily biodegradable in water. Biodegradability in soil: no data available. Adsorbs into the soil. Low potential for Mobility in soil. Photooxidation in the air.

12.3. Bioaccumulative potential

Colour Intensifier	
Bioaccumulative potential	Not established.
naphtha (petroleum), hydrotreated heavy (contains less than 0,1 % w/w benzene) (64742-48-9)	
Bioaccumulative potential	bioaccumulable.

12.4. Mobility in soil

naphtha (petroleum), hydrotreated heavy (contains less than 0,1 % w/w benzene) (64742-48-9)	
Surface tension	0,026 N/m (20 °C)

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to a licensed waste centre in accordance with local/regional/national/international regulations.

Additional information : Handle empty containers with care because residual vapours are flammable.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

European List of Waste (LoW) code : 20 01 13* - solvents

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 1300

14.2. UN proper shipping name

Proper Shipping Name (ADR) : TURPENTINE SUBSTITUTE

Transport document description (ADR) : UN 1300 TURPENTINE SUBSTITUTE, 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS





TILE AND STONE SURFACE PROTECTION

LTP GROUT PROTECTOR

CLEANING, SEALING AND AFTERCARE SOLUTIONS

according to Regulation (EC) No. 453/2010 Date of issue: 24/06/2015 Revision date: 06/07/2015

14.3. Transport hazard class(es)

Class (ADR) : 3
Danger labels (ADR) : 3



14.4. Packing group

Packing group (ADR) : III

14.5. Environmental hazards

Dangerous for the environment :



Other information : No supplementary information available.

14.6. Special precautions for user

14.6.1. Overland transport

Hazard identification number (Kemler No.) : 30
Classification code (ADR) : F1
Orange plates :



Transport category (ADR) : 3
Tunnel restriction code (ADR) : D/E
Limited quantities (ADR) : 5l
Excepted quantities (ADR) : E1
EAC code : 3YE

14.6.2. Transport by sea

No additional information available

14.6.3. Air transport

No additional information available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	Colour Intensifier - Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) - naphtha (petroleum), hydrotreated heavy (contains less than 0,1 % w/w benzene) - hydrocarbons, C9, aromatics
3.a. Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	Colour Intensifier - Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) - hydrocarbons, C9, aromatics
3.b. Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	Colour Intensifier - Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) - naphtha (petroleum), hydrotreated heavy (contains less than 0,1 % w/w benzene) - hydrocarbons, C9, aromatics
3.c. Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	Colour Intensifier - Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) - hydrocarbons, C9, aromatics

7 of 8



TONE ESTATE, MILVERTON ROAD, WELLINGTON SOMERSET, TA21 0AN

TEL:01823 666213

FAX:01823 665685

Email: info@ltp-online.co.uk

Technical Email:technical@ltp-online.co.uk

www.ltp-online.co.uk





TILE AND STONE SURFACE PROTECTION

LTP GROUT PROTECTOR

CLEANING, SEALING AND AFTERCARE SOLUTIONS

according to Regulation (EC) No. 453/2010 Date of issue: 24/06/2015 Revision date: 06/07/2015

40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

Colour Intensifier - Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) - naphtha (petroleum), hydrotreated heavy (contains less than 0,1 % w/w benzene) - hydrocarbons, C9, aromatics

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

Water hazard class (WGK) : 3 - severe hazard to waters

WGK remark : Classification water polluting based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 4)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of R-, H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H372	Causes damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects
EUH066	Repeated exposure may cause skin dryness or cracking
R10	Flammable
R37	Irritating to respiratory system
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R65	Harmful: may cause lung damage if swallowed
R66	Repeated exposure may cause skin dryness or cracking
R67	Vapours may cause drowsiness and dizziness
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful

SDS EU_NSC

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

