

CLEANING SEALING & AFTERCARE

PORCELAIN FLOOR TILE AFTERCARE CLEANER TECHNICAL DATA SHEET

REF: 10/5/1 OCTOBER 2024



LTP PORCELAIN FLOOR CLEANER

Gentle PH Neutral Cleaner

For Interior & Exterior use.

Suitable for all types of Porcelain and Ceramic Tile

A gentle cleaner especially formulated to clean porcelain and ceramic without damaging the grout or tile. Leaving the floor with a fresh clean fragrance.

Suitable for use on both sealed and un-sealed, polished and unpolished surfaces.

Directions for use

For application and cleaning tools see LTP website

Dilute 2 or 3 capfuls (5 capfuls on dirtier floors) in a bucket of warm water. Wash the floor and allow to dry. Does not require rinsing.

Coverage

1 litre of LTP Porcelain Floor Tile Cleaner should be sufficient to wash an average floor of 20m² approx 40 times.

Notes

Important: Polished surfaces & highly glazed tiles finish by buffing with a dry soft cloth or machine.

Contains 5% or over but less than 15% anionic surfactant. 5% or over but less than 15% non-ionic surfactant.

Perfume.

Ingredients: www.ltp-online.co.uk/dr

Storage information

Store in a cool, dry, frost-free environment.

Shelf Life – Up to 5 years.

Health, Safety & Environmental

Contains: Amides, C8-18 and C18-unsatd., N,N-bis(hydroxyethyl); Benzenesulfonic acid, 4- C10-13-sec-alkyl derivs., compds. With triethanolamine; SODIUM C14-16 OLEFIN SULFONATE

Health, Safety & Environmental cont...

Causes serious eye damage

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Wear protective gloves, protective clothing, eye protection.

IF ON SKIN: Wash with plenty of water

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE, a doctor.

Dispose of contents/container in accordance with local, regional, national and /or international regulation.

Danger



Only applies to concentrate: Not applicable once diluted

Label in accordance with EC No 1272/2008

UFI: ESD0-90GT-800A-YJHS



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline
+ 44 (0) 1823 666213 | www.ltp-online.co.uk | technical@ltp-online.co.uk
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN

