

Instruction Guide 12

GLAZED CERAMIC AND PORCELAIN TILES

Glazed tiles have a completely closed surface that is normally hard wearing and easy to maintain. Sealing is not normally required, however on some tiles it is possible to enhance their appearance and make them even easier to maintain. The following guide will help keep your floor tiles maintained and in good condition for many years.

THE 3 STEP INSTRUCTION OVERVIEW (see page 2 for more information)

1

LTP Grout Stain Remover

Coverage 1 litre/25m²



INITIAL CLEANING OF NEWLY INSTALLED SURFACES IF REQUIRED (used surfaces see page 2).

LTP GROUT STAIN REMOVER: Cleans and removes cement and grout residues. Conditions the surface of the tile.




Dilute Grout Stain Remover 1:3 with water.




Apply solution to the surface with a mop or sponge Under floor heating must be off.



Agitate with a nylon pad or scrubbing brush.



Rinse well with clean water.



Allow the surface to dry.

EQUIPMENT: Bucket, mop, scrubber.

2


LTP Glaze Protector

Coverage 1 litre/10m²




ENHANCE APPEARANCE AND EASE MAINTENANCE (for more information see page 2).


LTP GLAZE PROTECTOR: Satin finish – the just washed look – protects against dirt, grime, aids maintenance.



Surfaces must be clean and dry. Under floor heating must be off.



Apply the product to the surface evenly using a damp soft cloth or sponge.



Allow to dry Do not walk on the surface for at least 1 hour.



Protect from water for 24 hours and do not wash surfaces for at least 3 days.

EQUIPMENT: Bucket, applicator, damp soft cloth or sponge.

3

LTP Floorshine



REGULAR MAINTENANCE (for more information see page 2).


LTP FLOORSHINE: Maintains glazed ceramic and porcelain surfaces. Also maintains surfaces that have been enhanced with LTP Glaze Protector.



Add one capful of product per litre of water in a bucket.



Wash surface with the solution. Do not rinse.



Allow to dry. Do not walk on the surface during drying time – 20 minutes.

A one litre LTP Floorshine will wash a 20 sq.m floor 40 times.

EQUIPMENT: Bucket, mop.

Always read the product label before proceeding.

NEWLY INSTALLED SURFACES

AFTER GROUTING: Residual grout will normally remain visible on darker textured surfaces. For best results use LTP Grout Stain Remover to wash the surface and remove residues.

1

CLEANING: used and heavily soiled surfaces

- Dilute LTP Grimex 1:3 with water, apply to the surface with a sponge or water brush and leave to sit on the surface of the tiles for as long as it takes for the dirt to release. 5-30 minutes depending upon the level of dirt. (Work in manageable areas at a time and keep treated areas wet – do not allow the solution to dry on to the surface).
- Agitate the surface and grout joints with a nylon pad or scrubbing brush and leave for a further 5 minutes (scrubber machines can be used).
- Continue to scrub while adding clean water. Remove residues from the surface using a sponge, mop or scrubber dryer machine.
- Rinse thoroughly with clean fresh water to remove all remaining residues.
- If you are coating the surface with LTP Glaze Protector, tiles must be thoroughly cleaned. Ground in dirt, grime, residues from aftercare products and deposits must be removed from the surface.
- LTP Glaze Protector will help aid cleaning on more textured surfaces and simplify the removal of spillages.
- For best results LTP Glaze Protector should be applied using a lint free cloth saturated with the solution.
- If you are unsure please call our helpline for advice.

2

MAINTENANCE IN KITCHENS AND BATHROOMS

- LTP Multiclean used routinely will degrease and descale glazed ceramic and porcelain at the same time.
- LTP Multiclean leaves an invisible barrier of protection that helps to prevent the reformation of limescale. Simply spray on, leave for a few minutes, agitate and then rinse with water and a sponge.
- LTP Mouldex will remove mould and mildew on cement and silicone grout lines. Simply spray on to the effected area and allow to work for approximately 20 minutes before agitating and rinsing.
- LTP Floorshine is ideal for routine cleaning of glazed ceramic and porcelain tiles. Simply add a cap full of product per litre of water in a bucket, mop surfaces and leave to dry. Do not rinse.

NB. Always test the products on an inconspicuous area before general application. LTP Glaze Protector should not be used in wet areas such as shower enclosures.

3

MAINTENANCE

LTP FLOORSHINE (for floors)

Cleans and protects in one application. Used routinely it will reinforce protection offered by LTP Glaze Protector. Ideal for routine maintenance of glazed ceramic and porcelain.

LTP MULTICLEAN

Cleans and protects surfaces from limescale. Ideal for use in kitchens and bathrooms.

LTP MOULDEX

Cleans dirty grouting. Removes mould and grime. Restores white grouting to its original colour.



NB. Always follow the detailed instructions on the product labels. Avoid using normal detergents or strong bleach cleaners on any sealed surfaces as they will gradually remove the protective seal.

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.
© Copyright A.M.Robb Ltd. 2012