

# TM3217 & TM3267 Mech



The new ISEKI TM3267 is a versatile 25hp diesel compact tractor with a F8/R8 mechanical transmission. The ISO-mounted operator's platform combined with ergonomically positioned controls ensures operator comfort during extended working periods. The 3-point linkage has a lift capacity of 600kg or 800kg (TM3267 only) when fitted with the high-capacity lift kit.

The tractor features as standard, a rear-PTO, two double acting valves, mid-PTO, two double-acting auxiliary valves (one for TM3217), weight frame and a choice of AG or Turf tyres. The ISEKI TM3217 shares the same chassis, powered by a 19hp diesel engine. A front loader is optionally available for both models.



## KEY FEATURES

- Power:** 19hp @ 2600rpm or 24.4hp @ 2500rpm
- Speed:** 600kg or 800kg with high capacity lift kit (TM3267 only)
- Drive System:** Mechanical
- Special features:** ISO Mounted operators platform



		TM3217 Mech	TM3267 Mech
<b>Power</b>	Engine: Type	Diesel indirect injection, overhead valve	Diesel indirect injection, overhead valve
	Displacement	1123cc	1498cc
	No of cylinders	3	3
	Power	14.3kW (19hp) at 2600rpm	18.2kW (24.4hp) at 2500rpm
	Fuel capacity	28ltr (7.4gal)	28ltr (7.4gal)
	Rated engine speed	2600rpm	2500rpm
<b>Transmission</b>	Main Clutch	F8/R8	F8/R8
	No of speeds	8	8
	Forward	0.5-22.1kph (0-13.7mph)	0.5-24.4kph (0-15.2mph)
	Driven Wheels	4WD	4WD
	Differential Lock	Standard	Standard
<b>Brakes</b>	Type	Wet discs	Wet discs
<b>Tyres</b>	Type	Turf or Ag	Turf or Ag
	Front	6-12 (Ag) 24x8.50-12 (Turf)	6-12 (Ag) 24x8.50-12 (Turf)
	Rear	9.5-16 (Ag) 315/75D-15 (Turf)	9.5-18 (Ag) 315/75D-15 (Turf)
<b>Rear PTO</b>		1 speed 540 @ 2475rpm	1 speed 540 @ 2475rpm
<b>Mid PTO</b>		1 speed 2000 @ 2461rpm	1 speed 2000 @ 2461rpm
<b>PTO</b>	Shaft	1 3/8" 6-spline	1 3/8" 6-spline
<b>Hydraulic</b>	Lift capacity	600kg (1332lb)	600kg (1332lb) or 800kg (1764lb) with high capacity lift kit
	Pump Capacity ltr/m	20.0	20.8
	Position Control	Standard	Standard
	Rear linkage type	Category 1	Category 1
<b>ROPS</b>	Type	Rear foldable	Rear foldable
<b>Dimensions</b>	Length	2.815m (110.8")	2.88m (113.4")
	Width	1.1m (43.7") (Ag tyres) 1.295m (51") (Turf tyres)	1.1m (43.7") (Ag tyres) 1.295m (51") (Turf tyres)
	Height	2.39m	2.39m
	Weight	835kg (1841lb)	870kg (1918lb)
	Ground Clearance	0.25m (9.8")	0.25m (9.8")

