

TXG237



The TXG237 benefits from a flat easy-access platform, clear automotive style dashboard and controls, with switchable four-wheel drive makes the TXG237 very user friendly. Individual forward and reverse pedals give the operator precise control.

Its compact dimensions and powerful 23hp diesel engine makes the TXG237 a multi-purpose grounds care tractor. Robust enough to take a front loader or back hoe and other implements via a Cat 1 3-point hitch including collectors and centre mounted mowing decks; this is a versatile machine for any application.



KEY FEATURES

Power: 23hp (16.8kW)

Lift capacity: 540kg at ball ends

Special features: Independent PTO, high ground clearance, includes auxillary hydraulic valve with two double acting spools, easily attached/detached mower deck

Power	Engine: Type	Diesel indirect injection, overhead valve
	Displacement	1123cc
	No of cylinders	3
	Power	16.8kW (23hp) at 2600rpm
	Fuel capacity	21ltr (4.6gal)
	Rated engine speed	2600rpm
Transmission	Type	Hydrostatic
	Gear forward/reverse	2/2
	Speed	0 to 14.3km/h (8.8mph)
	Driven Wheels	4WD
	Differential Lock	Standard
Brakes	Type	Wet discs
Tyres	Type	Turf or Semi-Ag
	Front	18 x 8.50-8
	Rear	26 x 12.0-12
PTO	Engagement	Hydraulic
	Rear PTO at engine rpm	540 @ 2532rpm
	Mid PTO at engine rpm	2000 @ 2476rpm
Hydraulics	Steering	Hydrostatic (power)
	Main System	Transmission mounted gear pup with flow divider
	Max output	23.1 ltr/min (5.1gal/min) @ 2500rpm
	Three point lift	Category 1
	Lift Capacity	540kg (1190lb) at ball end
ROPS	Type	Rear foldable
Dimensions	Length	2.48m (97.6")
	Width	1.19m (47")
	Height with ROPS	2.25m (88")
	Weight with ROPS	665kg (1463lb)
	Ground Clearance	215mm (8.4")
	Wheelbase	1.45m (57")
	Weight	575kg
Mower Deck	1.22m (48") side and rear discharge	
	1.37m (54") side and rear discharge	
	1.5m (60") side discharge	
	1.37m (54") mulching	
Optional Equipment	550 litre low dump collector with 540rpm blower and collector frame available	